

Trimmer Potentiometers




BOURNS®

Lead Sealed Type Multiturn PV12 Series

PV12 Series

■ Features

1. Multiturn / Cermet / Sealed
2. Available in both top and side adjustment
3. RoHS compliant*
4. For trimmer applications/processing guidelines,
[click here](#)


PV12P

PV12T


Top Adjustment

Part Number	Power Rating (W)	Number of Turns (Effective Rotation Angle)	Total Resistance Value	TCR (ppm/°C)
PV12P100A01B00	0.5 (70 °C)	4	10 ohm $\pm 10\%$	± 100
PV12P200A01B00	0.5 (70 °C)	4	20 ohm $\pm 10\%$	± 100
PV12P500A01B00	0.5 (70 °C)	4	50 ohm $\pm 10\%$	± 100
PV12P101A01B00	0.5 (70 °C)	4	100 ohm $\pm 10\%$	± 100
PV12P201A01B00	0.5 (70 °C)	4	200 ohm $\pm 10\%$	± 100
PV12P501A01B00	0.5 (70 °C)	4	500 ohm $\pm 10\%$	± 100
PV12P102A01B00	0.5 (70 °C)	4	1k ohm $\pm 10\%$	± 100
PV12P202A01B00	0.5 (70 °C)	4	2k ohm $\pm 10\%$	± 100
PV12P502A01B00	0.5 (70 °C)	4	5k ohm $\pm 10\%$	± 100
PV12P103A01B00	0.5 (70 °C)	4	10k ohm $\pm 10\%$	± 100
PV12P203A01B00	0.5 (70 °C)	4	20k ohm $\pm 10\%$	± 100
PV12P253A01B00	0.5 (70 °C)	4	25k ohm $\pm 10\%$	± 100
PV12P503A01B00	0.5 (70 °C)	4	50k ohm $\pm 10\%$	± 100
PV12P104A01B00	0.5 (70 °C)	4	100k ohm $\pm 10\%$	± 100
PV12P204A01B00	0.5 (70 °C)	4	200k ohm $\pm 10\%$	± 100
PV12P254A01B00	0.5 (70 °C)	4	250k ohm $\pm 10\%$	± 100
PV12P504A01B00	0.5 (70 °C)	4	500k ohm $\pm 10\%$	± 100
PV12P105A01B00	0.5 (70 °C)	4	1M ohm $\pm 10\%$	± 100

Operating Temperature Range: -55 to +125 °C

Soldering Method: Wave (Single and Dual)

BOURNS®

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.
Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.



Side Adjustment

Part Number	Power Rating (W)	Number of Turns (Effective Rotation Angle)	Total Resistance Value	TCR (ppm/°C)
PV12T100A01B00	0.5 (70°C)	4	10 ohm ± 10 %	±100
PV12T200A01B00	0.5 (70°C)	4	20 ohm ± 10 %	±100
PV12T500A01B00	0.5 (70°C)	4	50 ohm ± 10 %	±100
PV12T101A01B00	0.5 (70°C)	4	100 ohm ± 10 %	±100
PV12T201A01B00	0.5 (70°C)	4	200 ohm ± 10 %	±100
PV12T501A01B00	0.5 (70°C)	4	500 ohm ± 10 %	±100
PV12T102A01B00	0.5 (70°C)	4	1k ohm ± 10 %	±100
PV12T202A01B00	0.5 (70°C)	4	2k ohm ± 10 %	±100
PV12T502A01B00	0.5 (70°C)	4	5k ohm ± 10 %	±100
PV12T103A01B00	0.5 (70°C)	4	10k ohm ± 10 %	±100
PV12T203A01B00	0.5 (70°C)	4	20k ohm ± 10 %	±100
PV12T253A01B00	0.5 (70°C)	4	25k ohm ± 10 %	±100
PV12T503A01B00	0.5 (70°C)	4	50k ohm ± 10 %	±100
PV12T104A01B00	0.5 (70°C)	4	100k ohm ± 10 %	±100
PV12T204A01B00	0.5 (70°C)	4	200k ohm ± 10 %	±100
PV12T254A01B00	0.5 (70°C)	4	250k ohm ± 10 %	±100
PV12T504A01B00	0.5 (70°C)	4	500k ohm ± 10 %	±100
PV12T105A01B00	0.5 (70°C)	4	1M ohm ± 10 %	±100

Operating Temperature Range: -55 to +125 °C

Soldering Method: Wave (Single and Dual)

■ Standard Mounting Holes



DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$

TOLERANCES: $\pm \frac{0.1}{(0.004)}$

EXCEPT WHERE NOTED

BOURNS®

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.

■ Characteristics

Temperature Cycle	ΔTR : $\pm 2\%$ $\Delta V.S.S.$: $\pm 1\%$
Humidity	ΔTR : $\pm 2\%$ IR : 100M ohm min.
Vibration (20G)	ΔTR : $\pm 1\%$ $\Delta V.S.S.$: $\pm 1\%$
Shock (100G)	ΔTR : $\pm 1\%$ $\Delta V.S.S.$: $\pm 1\%$
Temperature Load Life	ΔTR : $\pm 3\%$ $\Delta V.S.S.$: $\pm 2\%$
Low Temperature Exposure	ΔTR : $\pm 3\%$ $\Delta V.S.S.$: $\pm 1.5\%$
High Temperature Exposure	ΔTR : $\pm 3\%$ $\Delta V.S.S.$: $\pm 1.5\%$
Rotational Life	ΔTR : $\pm 3\%$ (200 cycles)

ΔTR : Total Resistance Change
 $\Delta V.S.S.$: Voltage Setting Stability
 IR : Insulation Resistance

■ Typical Part Marking

3-Digit Date Code and Manufacturing Code

- First digit indicates year of manufacture;
- Last two digits indicate week of manufacture;
- 4th digit is suffix for manufacturing location:
C = Costa Rica

Example:

604C = Manufactured in 2016, week 4, Costa Rica

Resistance Code

- Resistance code marking as shown in the
Part Numbering Resistance Table.

■ Part Numbering

PV 12 P 103 A01 B00

Product ID _____
PV = Trimming Potentiometer

Series _____
12 = Lead Sealed 7 mm Round, 4-Turns

Adjustment Direction/Lead Type _____
P = Top, Triangle
T = Side, Triangle

Total Resistance _____
Expressed by three figures.
The first and second figures are significant digits;
the third figure expresses the number of zeros
that follow.

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105

Popular distribution resistance values listed in boldface. Special resistances available.

Individual Specification _____
A01 = Standard Type

Packaging _____
B00 = Tube (50 pcs. per tube)

BOURNS®

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

<u>PV12P204A01B00</u>	<u>PV12P202A01B00</u>	<u>PV12P201A01B00</u>	<u>PV12P205A01B00</u>	<u>PV12P504A01B00</u>	
<u>PV12P500A01B00</u>	<u>PV12P100A01B00</u>	<u>PV12P102A01B00</u>	<u>PV12P105A01B00</u>	<u>PV12P103A01B00</u>	<u>PV12T205A01B00</u>
<u>PV12T201A01B00</u>	<u>PV12T203A01B00</u>	<u>PV12T202A01B00</u>	<u>PV12T204A01B00</u>	<u>PV12T200A01B00</u>	<u>PV12T503A01B00</u>
<u>PV12T501A01B00</u>	<u>PV12T500A01B00</u>	<u>PV12T504A01B00</u>	<u>PV12T502A01B00</u>	<u>PV12T102A01B00</u>	<u>PV12T104A01B00</u>
<u>PV12T100A01B00</u>	<u>PV12T103A01B00</u>	<u>PV12T101A01B00</u>	<u>PV12T105A01B00</u>	<u>PV12P253A01B00</u>	<u>PV12T254A01B00</u>
<u>PV12T253A01B00</u>	<u>PV12P254A01B00</u>				