

# Sta-Kon® Terminals



These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wire's flex point. Braided seam barrel is serrated for high pull-out value. Terminal is high conductivity electrolytic copper, electro-tin plated. Insulation is color-coded.


Stock thickness same as ring terminal of same size.

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 190-191. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

## Vinyl Insulated Fork – Insulation Support

| Cat. No. | Pkg. Qty. | Wire Range | Max. Ins. | Bolt Hole | Wt./Lbs. Per 1000 | Dimensions |     |     |     |
|----------|-----------|------------|-----------|-----------|-------------------|------------|-----|-----|-----|
|          |           |            |           |           |                   | A          | B   | C   | M   |
| 18RA-6F  | 100       | 22-16      | .150      | #6        | 5                 | .94        | .25 | .27 | .81 |
| RA1167   | 1000      | 22-16      | .150      | #6        | 5                 | .94        | .25 | .27 | .81 |
| 18RA-8F  | 100       | 22-16      | .150      | #8        | 5                 | .97        | .31 | .27 | .81 |
| RA1147   | 1000      | 22-16      | .150      | #8        | 5                 | .97        | .31 | .27 | .81 |
| 18RA-10F | 100       | 22-16      | .150      | #10       | 5                 | .97        | .31 | .27 | .81 |
| RA1157   | 1000      | 22-16      | .150      | #10       | 5                 | .97        | .31 | .27 | .81 |
| 14RB-6F  | 100       | 18-14      | .170      | #6        | 6                 | .97        | .31 | .27 | .81 |
| RB647    | 1000      | 18-14      | .170      | #6        | 6                 | .97        | .31 | .27 | .81 |
| 14RB-6FS | 100       | 18-14      | .170      | #6        | 6                 | .89        | .30 | .25 | .75 |
| 14RB-8F  | 100       | 18-14      | .170      | #8        | 6                 | .97        | .31 | .27 | .81 |
| RB657    | 1000      | 18-14      | .170      | #8        | 6                 | .97        | .31 | .27 | .81 |
| 14RB-10F | 100       | 18-14      | .170      | #10       | 6                 | .97        | .31 | .27 | .81 |
| RB1157   | 1000      | 18-14      | .170      | #10       | 6                 | .97        | .31 | .27 | .81 |
| 14RB-14F | 100       | 18-14      | .170      | 1/4"      | 6                 | 1.11       | .44 | .38 | .89 |
| RB1717   | 1000      | 18-14      | .170      | 1/4"      | 6                 | 1.11       | .44 | .38 | .89 |
| 10RC-6F  | 50        | 12-10      | .210      | #6        | 7                 | 1.09       | .38 | .27 | .90 |
| RC1337   | 500       | 12-10      | .210      | #6        | 7                 | 1.09       | .38 | .27 | .90 |
| 10RC-8F  | 50        | 12-10      | .210      | #8        | 7                 | 1.09       | .38 | .27 | .90 |
| RC1147   | 500       | 12-10      | .210      | #8        | 7                 | 1.09       | .38 | .27 | .90 |
| 10RC-10F | 50        | 12-10      | .210      | #10       | 7                 | 1.09       | .38 | .27 | .90 |
| RC1157   | 500       | 12-10      | .210      | #10       | 7                 | 1.09       | .38 | .27 | .90 |
| 10RC-14F | 50        | 12-10      | .210      | 1/4"      | 7                 | 1.15       | .50 | .37 | .90 |
| RC1167   | 500       | 12-10      | .210      | 1/4"      | 7                 | 1.15       | .50 | .37 | .90 |

U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003, WT2130A(RC)



Fork terminals allow easy installation since the mounting screw does not have to be completely removed. Catalog numbers with the suffix X indicate an expanded insulation support. This means a wider wire entry to accommodate heavy wall insulation.

Stock thickness same as ring terminal of same size.

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 190-191. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

## Vinyl Insulation Fork – Expanded Insulation Support

| Cat. No.   | Pkg. Qty. | Wire Range | Max. Ins. | Bolt Hole | Wt./Lbs. Per 1000 | Dimensions |     |     |     |
|------------|-----------|------------|-----------|-----------|-------------------|------------|-----|-----|-----|
|            |           |            |           |           |                   | A          | B   | C   | M   |
| 18RA-6FX   | 100       | 22-16      | .170      | #6        | 5                 | .94        | .25 | .27 | .81 |
| RA1167-170 | 1000      | 22-16      | .170      | #6        | 5                 | .94        | .25 | .27 | .81 |
| 18RA-8FX   | 100       | 22-16      | .170      | #8        | 5                 | .97        | .31 | .27 | .81 |
| RA1147-170 | 1000      | 22-16      | .170      | #8        | 5                 | .97        | .31 | .27 | .81 |
| 18RA-10FX  | 100       | 22-16      | .170      | #10       | 5                 | .97        | .31 | .27 | .81 |
| RA1157-170 | 1000      | 22-16      | .170      | #10       | 5                 | .97        | .31 | .27 | .81 |
| 14RB-6FX   | 100       | 18-14      | .200      | #6        | 6                 | .97        | .31 | .27 | .81 |
| RB647-200  | 1000      | 18-14      | .200      | #6        | 6                 | .97        | .31 | .27 | .81 |
| 14RB-8FX   | 100       | 18-14      | .200      | #8        | 6                 | .97        | .31 | .27 | .81 |
| RB657-200  | 1000      | 18-14      | .200      | #8        | 6                 | .97        | .31 | .27 | .81 |
| 14RB-10FX  | 100       | 18-14      | .200      | #10       | 6                 | .97        | .31 | .27 | .81 |
| RB1157-200 | 1000      | 18-14      | .200      | #10       | 6                 | .97        | .31 | .27 | .81 |
| 10RC-8FX   | 50        | 12-10      | .250      | #8        | 7                 | 1.11       | .38 | .27 | .90 |
| RC1147-250 | 500       | 12-10      | .250      | #8        | 7                 | 1.11       | .38 | .27 | .90 |
| 10RC-10FX  | 50        | 12-10      | .250      | #10       | 7                 | 1.11       | .38 | .27 | .90 |
| RC1157-250 | 500       | 12-10      | .250      | #10       | 7                 | 1.11       | .38 | .27 | .90 |
| 10RC-14FX  | 50        | 12-10      | .250      | 1/4"      | 7                 | 1.17       | .50 | .37 | .90 |

U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG2001, ERG2003 WT2130A(RC)

