

## 2A, 120V, 1.750 Ohm, Logic Level, N-Channel Power MOSFET

The RFP2N12L is an N-Channel enhancement mode silicon gate power field effect transistor specifically designed for use with logic level (5V) driving sources in applications such as programmable controllers, automotive switching, and solenoid drivers. This performance is accomplished through a special gate oxide design which provides full rated conduction at gate biases in the 3V - 5V range, thereby facilitating true on-off power control directly from logic circuit supply voltages.

Formerly developmental type TA09528.

### Ordering Information


PART NUMBER	PACKAGE	BRAND
RFP2N12L	TO-220AB	RFP2N12L

NOTE: When ordering, include the entire part number.

### Features


- 2A, 120V
- $r_{DS(ON)} = 1.750\Omega$
- Design Optimized for 5V Gate Drives
- Can be Driven Directly from QMOS, NMOS, TTL Circuits
- Compatible with Automotive Drive Requirements
- SOA is Power Dissipation Limited
- Nanosecond Switching Speeds
- Linear Transfer Characteristics
- High Input Impedance
- Majority Carrier Device
- Related Literature
  - TB334 "Guidelines for Soldering Surface Mount Components to PC Boards"

### Symbol



### Packaging

JEDEL TO-220AB



## Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

		RFP2N12L	UNITS
Drain to Source Voltage (Note 1) . . . . .	$V_{DSS}$	120	V
Drain to Gate Voltage $R_{GS} = 20\text{ k}\Omega$ (Note 1) . . . . .	$V_{DGR}$	120	V
Gate to Source Voltage . . . . .	$V_{GS}$	$\pm 10$	V
Continuous Drain Current . . . . .	$I_D$	2	A
Pulsed Drain Current (Note 3) . . . . .	$I_{DM}$	5	A
Maximum Power Dissipation . . . . .	$P_D$	25	W
Derate Above $T_C = 25^\circ\text{C}$ . . . . .		0.2	W/ $^\circ\text{C}$
Operating and Storage Temperature . . . . .	$T_J, T_{STG}$	-55 to 150	$^\circ\text{C}$
Maximum Temperature for Soldering Leads at 0.063in (1.6mm) from Case for 10s . . . . .	$T_L$	300	$^\circ\text{C}$
Package Body for 10s, See Techbrief 334 . . . . .	$T_{pkg}$	260	$^\circ\text{C}$

*CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.*

### NOTE:

1.  $T_J = 25^\circ\text{C}$  to  $125^\circ\text{C}$ .

## Electrical Specifications $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Drain to Source Breakdown Voltage	$BV_{DSS}$	$I_D = 250\mu\text{A}, V_{GS} = 0$	120	-	-	V
Gate to Threshold Voltage	$V_{GS(\text{TH})}$	$V_{GS} = V_{DS}, I_D = 250\mu\text{A}$ (Figure 8)	1	-	2	V
Zero-Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = \text{Rated } BV_{DSS}, V_{GS} = 0\text{V}$	-	-	1	$\mu\text{A}$
		$V_{DS} = 0.8 \times \text{Rated } BV_{DSS}, V_{GS} = 0\text{V}, T_C = 125^\circ\text{C}$	-	-	25	$\mu\text{A}$
Gate to Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 10\text{V}, V_{DS} = 0\text{V}$	-	-	$\pm 100$	nA
Drain to Source On Voltage (Note 2)	$V_{DS(\text{ON})}$	$I_D = 2\text{A}, V_{GS} = 5\text{V}$	-	-	3.5	V
Drain to Source On Resistance (Note 2)	$r_{DS(\text{ON})}$	$I_D = 2\text{A}, V_{GS} = 5\text{V}$ (Figure 6, 7)	-	-	1.750	$\Omega$
Turn-On Delay Time	$t_{d(\text{ON})}$	$I_D \approx 2\text{A}, V_{DD} = 75\text{V}, R_G = 6.25\Omega, R_L = 75\Omega, V_{GS} = 5\text{V}$ (Figures 10, 11, 12)	-	10	25	ns
Rise Time	$t_r$		-	10	45	ns
Turn-Off Delay Time	$t_{d(\text{OFF})}$		-	24	45	ns
Fall Time	$t_f$		-	20	25	ns
Input Capacitance	$C_{ISS}$	$V_{GS} = 0\text{V}, V_{DS} = 25\text{V}, f = 1\text{MHz}$ (Figure 9)	-	-	200	pF
Output Capacitance	$C_{OSS}$		-	-	80	pF
Reverse Transfer Capacitance	$C_{RSS}$		-	-	35	pF
Thermal Resistance Junction to Case	$R_{\theta JC}$		-	-	5	$^\circ\text{C/W}$


## Source to Drain Diode Specifications

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Source to Drain Diode Voltage (Note 2)	$V_{SD}$	$I_{SD} = 2\text{A}$	-	-	1.4	V
Diode Reverse Recovery Time	$t_{rr}$	$I_{SD} = 2\text{A}, dI_{SD}/dt = 50\text{A}/\mu\text{s}$	-	150	-	ns


### NOTES:

2. Pulsed: pulse duration =  $300\mu\text{s}$  max, duty cycle = 2%.
3. Repetitive rating: pulse width limited by maximum junction temperature.


**Typical Performance Curves** Unless Otherwise Specified




**FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE**




**FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE**




**FIGURE 3. FORWARD BIAS SAFE OPERATING AREA**



**FIGURE 4. SATURATION CHARACTERISTICS**




**FIGURE 5. TRANSFER CHARACTERISTICS**




**FIGURE 6. DRAIN TO SOURCE ON RESISTANCE vs DRAIN CURRENT**


**Typical Performance Curves** Unless Otherwise Specified (Continued)




**FIGURE 7. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE**



**FIGURE 8. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE**




**FIGURE 9. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE**




NOTE: Refer to Intersil Applications Notes AN7254 and AN7260

**FIGURE 10. NORMALIZED SWITCHING WAVEFORMS FOR CONSTANT GATE CURRENT**

**Test Circuits and Waveforms**



**FIGURE 11. SWITCHING TIME TEST CIRCUIT**



**FIGURE 12. RESISTIVE SWITCHING WAVEFORMS**

All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

*Intersil semiconductor products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

---

For information regarding Intersil Corporation and its products, see web site <http://www.intersil.com>

### **Sales Office Headquarters**

#### **NORTH AMERICA**

Intersil Corporation  
P. O. Box 883, Mail Stop 53-204  
Melbourne, FL 32902  
TEL: (407) 724-7000  
FAX: (407) 724-7240

#### **EUROPE**

Intersil SA  
Mercure Center  
100, Rue de la Fusée  
1130 Brussels, Belgium  
TEL: (32) 2.724.2111  
FAX: (32) 2.724.22.05

#### **ASIA**

Intersil (Taiwan) Ltd.  
7F-6, No. 101 Fu Hsing North Road  
Taipei, Taiwan  
Republic of China  
TEL: (886) 2 2716 9310  
FAX: (886) 2 2715 3029