


SPECIFICATIONS						
CONTACT CARRIER MATERIAL/COLOR	NYLON or TPU/BLACK					
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW					
CONTACT MATERIAL/PLATING	BRASS/GOLD					
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL					
RATED CURRENT [A]	2.0 A					
RATED VOLTAGE [V]	60 VAC/75 VDC					
OUTER CABLE JACKET MATERIAL/COLOR	PVC/GRAY					
CONDUCTOR INSULATION MATERIAL	PVC					
NUMBER OF CONDUCTORS [AWG]	10x24 AWG					
DRAIN/SHIELD	26 AWG/BRAIDED AND FOIL SHIELD					
TEMPERATURE RANGE	-40°C to +105°C (-40°F to 221°F)					
PROTECTION CLASS	MEETS IEC IP67					



CABLE LENGTH	TOLERANCE			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER TOLERANCE			
STRIP LENGTH				
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			

02/15/11

DATE

NOTES:

REV DESCRIPTION

UPDATE PROTECTION CLASS

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

		Z. THIS DOCUMENT		High Technology	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com			
		MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS	DRFT RWC	DATE 03/24/05 SCALE 1=1.0	DESCRIPTION RKS 10T-*-	-RSS 10T	
		DRAWING ARE FOR REFERENCE ONLY		UNIT OF ME	ASUREMENT	IDENTIFICATION NO.		REV
1	34226		CONTACT TURCK FOR MORE INFORMATION	MILLIMETE	ER [INCH]			D
T	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: 777003515	SHEET	1 OF 1

SOURCE DRAWING - FOR REFERENCE ONLY