

Power Relay RM 8

- 2 pole 25 A, 2 form C (2 CO) contacts
- DC or AC coil
- Mechanical indicator
- Push-to-test button
- Chassis or DIN rail mount

Typical applications
Cleaning equipment, heating and cooling equipment.



Approvals



VDE Cert. No. 40003144, UL E214025,
Technical data of approved types on request.

Contact Data

Contact arrangement	2 form C (CO)
Rated voltage	400VAC
Max. switching voltage	400VAC
Rated current	25A
Limiting making current, 20ms max.	60A
Switching power	6000VA
Contact material	AgCdO, AgNi90/10
Min. recommended contact load	24VDC/100mA
Frequency of operation, with/without load, DC coil	960/6000h ⁻¹
Operate/release time max., DC coil	15/10ms
Bounce time max., form A/form B, DC coil	4/6ms

Contact ratings

Type	Contact	Load	Cycles
IEC 61810			
RM8	C (CO)	25 A, 250 VAC, cosφ=1 35°C	10x10 ³
RM82	C (CO)	25 A, 250 VAC, cosφ=1 DC-coil, 65°C	10x10 ³
RM82	C (CO)	25 A, 250 VAC, cosφ=1 AC-coil, 40°C	10x10 ³
UL 508			
RM80	A/B (NO/NC)	25 A, 240 VAC, 1 phase per pole, general purpose 40°C	6x10 ³
RM8	A/B (NO/NC)	25 A, 415 VAC, resistive, 45°C	10x10 ³
RM82	A/B (NO/NC)	16 A, 415 VAC, resistive, 70°C	30x10 ³
RM82	A/B (NO/NC)	240 VAC, 1phase, 2HP, 50°C	6x10 ³
Mechanical endurance			
		10x10 ⁶ operations	



Power Relay RM 8 (Continued)
Coil Data (continued)
Coil versions, AC coil

Coil code STD	LED	Rated voltage VAC	Operate voltage 50/60Hz VAC	Release voltage 50/60Hz VAC	Coil resistance $\Omega \pm 10\%^{1)}\right)$	Rated coil power 50/60Hz VA
506	R06	6	4.8/5.1	1.8	4.7	2.86/2.36
512	R12	12	9.6/10.2	3.6	19.5	2.71/2.27
524	R24	24	19.2/20.4	7.2	80	2.62/2.00
548	R48	48	38.4/40.8	14.4	320	2.60/2.17
560	R60	60	48.0/51.0	18.0	500	2.62/2.20
615	S15	115	92.0/97.8	34.5	1850	2.65/2.22
730	T30	230	184.0/195.5	69.0	7500	2.69/2.26
900	V00	400	320.0/340.0	120.0	23500 ²⁾	2.61/2.20

2) Coil resistance $\pm 15\%$.

All figures are given for coil without pre-energization, at ambient temperature +23°C.

Insulation Data

Initial dielectric strength between open contacts	1500Vrms
between contact and coil	2500Vrms
between adjacent contacts	4000Vrms
Initial surge withstand voltage between contact and coil	5000V(1.2/50μs)
between adjacent contacts	6000V(1.2/50μs)
Clearance/creepage between contact and coil	$\geq 4.0/14.9\text{mm}$
between adjacent contacts	$\geq 15.3/15.3\text{mm}$
Material group of insulation parts	IIIa


Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content
refer to the Product Compliance Support Center at
www.te.com/customersupport/rohssupportcenter



Ambient temperature for mounting/handling in operation	-20 to +40°C
DC coil	-40 to +65°C
AC coil	-40 to +40°C
16 A contact load	-40 to +70°C
Category of environmental protection IEC 61810	RTI - dust protected
Vibration resistance (functional) form A (NO)/form B (NC)	10/5g, 30 to 150Hz
Terminal type	quick-connect
Cover retention, pull/push force	100/100N
Weight	81g
Packaging unit	10/25 pcs.

Terminal assignment

Bottom view on pins



Dimensions

Cover with mounting brackets, 6.3mm quick connect terminals




Cover with DIN-snap-on attachment

horizontal



vertical



Power Relay RM 8 (Continued)

Product code structure

 Typical product code **RM** **8** **0** **9** **024**

Type

RM Power relay RM8

Contact configuration

8 2 form C contacts (2 CO), 25A

Version

0	AgCdO, without test button	3	AgCdO, with test button
2	AgNi90/10, without test button	7	AgNi90/10, with test button

Enclosure

5	cover with mounting brackets, 6.3mm quick connect terminals
8	cover with DIN-snap-on attachment, horizontal, 6.3mm quick connect terminals
9	cover with DIN-snap-on attachment, vertical, 6.3mm quick connect terminals

Coil

Coil code: please refer to coil versions table

Product code	Contacts	Cont. material	Version	Enclosure	Coil	Coil	Part number
RM805024	2 form C, 2 CO contacts	AgCdO AgNi	Without test button	Mounting brackets quick c. 6.3 mm	DC-coil	24VDC	2-1393844-7 7-1415544-3
RM825024	25 A	AgCdO			AC-coil	24VAC 115VAC 230VAC	2-1393147-9 3-1393147-1 3-1393147-3
RM805524		AgCdO					5-1415544-8
RM805615		AgCdO					2-1393844-9
RM805730		AgCdO					3-1393147-7
RM825730		AgNi					5-1393149-8
RM808024		AgCdO		DIN-snap-on	DC-coil	24VDC	3-1393147-7
RM808524		AgCdO		horizontal	AC-coil	24VAC	2-1393149-7
RM808730		AgCdO				230VAC	3-1393149-8
RM809024		AgCdO		DIN-snap-on	DC-coil	24VDC	3-1393149-9
RM809615		AgCdO		vertical	AC-coil	115VAC	5-1393147-8
RM809730		AgCdO				230VAC	3-1393147-9
RM835024		AgCdO	With test button	mounting brackets quick c. 6.3 mm	DC-coil	24VDC	4-1393147-1
RM835524		AgCdO			AC-coil	24VAC	4-1393147-3
RM835615		AgCdO				115VAC	4-1393147-4
RM835730		AgCdO				230VAC	4-1393147-6
RM838024		AgCdO		DIN-snap-on	DC-coil	24VDC	4-1393147-8
RM838524		AgCdO		horizontal	AC-coil	24VAC	5-1393147-0
RM838730		AgCdO				230VAC	5-1393147-1
RM839024		AgCdO		DIN-snap-on	DC-coil	24VDC	5-1393147-4
RM839524		AgCdO		vertical	AC-coil	24VAC	5-1393147-5
RM839730		AgCdO				230VAC	5-1393147-6

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[RM835048](#)