

111-12300



Article Number: 111-12300

Description: Wide-Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

Base Data	Local Order Number	111-12300
	Type	WSS
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Wide strap is designed to minimize pinching of soft hoses and convoluted tubing. • Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles. • Clamping rails on the bottom of head to increase grip on round bundles. • Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles. • Bent tail allows for quick insertion into head or mounts.
	Quantity Per	bag
	Product Description	The Heavy Duty Wide-Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.
	GLOBAL PART NAME	WSS-PA66HIRHSUV-BK
	Short Description	Wide-Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		535.0N
Length L (Imperial)		9.1"
Length L (Metric)		231.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.5"

111-12300



Product Dimensions	Width W (Metric)	12.7mm
	Bundle Diameter Min. (Imperial)	0.375"
	Bundle Diameter Min. (Metric)	9.7mm
	Bundle Diameter Max. (Imperial)	2.25"
	Bundle Diameter Max. (Metric)	58.4mm
	Thickness T (Imperial)	0.055"
	Cable Tie Head Length (Imperial)	0.393"
	Cable Tie Head Width (Imperial)	0.78"
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	300
	Package Quantity (Metric)	300
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	0.0042kg
	Weight (imperial)	0.0092lbs