

Raychem Corporation

300 Constitution Drive
Menlo Park, CA 94025
800-227-4856
FAX 800-227-4866

R PolySwitch® PTC Devices Resettable Fuse

PRODUCT: RUE250

DOCUMENT: SCD 22053
PCN: 292247
REV LETTER: I
REV DATE: AUGUST 26, 1999
PAGE NO.: 1 OF 1

Specification Status: **RELEASED**

Electrical Rating

Voltage: 30V MAX
Current: 40A MAX

Insulating Material:

Cured, Flame Retarded Epoxy Polymer
meets UL94 V-0 Requirements

Lead Material:

24 AWG Tin/Lead Plated Copper Clad Steel

Marking:

Raychem Logc
and Voltage
XX 30
U250 — Part Identification
□□□□ — Lot Identification
(can be on back)




TABLE I. DIMENSIONS:

	A		B		C		D		E		F
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	TYP
mm:	--	11.4	--	18.3	4.3	5.8	7.6	--	--	3.0	--
in*:	--	(0.45)	--	(0.72)	(0.17)	(0.23)	(0.30)	--	--	(0.12)	--

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS:

I HOLD	CURRENT RATINGS						TIME TO TRIP	RESISTANCE		ONE-HOUR POST-TRIP RESISTANCE STANDARD TRIP	NOMINAL TRIPPED POWER DISSIPATION
	AMPS AT 0°C		AMPS AT 20°C		AMPS AT 60°C			OHMS AT 20°C			
AMPS 20°C HOLD	AMPS HOLD	AMPS TRIP	AMPS HOLD	AMPS TRIP	AMPS HOLD	AMPS TRIP	SECONDS AT 20°C, 12.5A MAX	OHMS MIN	OHMS MAX	OHMS AT 20°C MAX	WATTS AT 20°C
2.50	2.88	5.76	2.50	5.00	1.50	3.00	10.3	0.02	0.04	0.07	1.2

Recognitions:

UL/CSA/TUV approved

Reference Documents:

PS300

Precedence:

This specification takes precedence over documents referenced herein.

Effectivity:

Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION:

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.