Our commitment. Your advantage.

Search

My Account

Products

Documentation


Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>PolySwitch Resettable Devices</u> > <u>Product Feature Selector</u> > Product Details

RXE110-AP Product Details



RXE110-AP

TE Internal Number: 859033-000

Obsolete

Contact Product Information Center

PolySwitch Resettable Devices


Always ELV Compliant (Find RoHS Compliant Alternates/Statement of Compliance)

Product Highlights:

- Radial Application
- Family Name = RXE
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 1.1 Amps.
- IT (Room Temperature) = 2.20 Amps.

View all Features

Add to My Part List





Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:

• RXE110 (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

• None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

<u>Product Line Information</u>

Related Products:

Tooling

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 1.1
- IT (Room Temperature) (Amps.) = 2.20
- Vmax Operating (V) = 72
- Rmin(?) = 0.15
- Rmax(?) = 0.250
- R1 Max [Post Trip] (?) = 0.38
- Power Dissipation (Typical) (W) = 1.50

Termination Related Features:

• Construction = Radial, Through Hole

Body Related Features:

• Lead Type = Straight

Contact Related Features:

• Family Name = RXE

Configuration Related Features:

Coating = Coated

Industry Standards:

- RoHS/ELV Compliance = ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Always was ELV compliant
- TUV Certificate No. = R72041428

Conditions for Usage:

• Operating Temperature (Max.) (?C) = 85

Operation/Application:

Application = Radial

Packaging Related Features:

• Packaging Method = Ammo Pack

Other:

• Brand = Raychem

Provide Website Feedback | Need Help?