



DRAWING REVISIONS			
REV	DOCUMENT	APP	DATE
I	DO 06-1067		

NOTES:

- SPECIFICATIONS:
 - ELECTRICAL:
 - OPERATING VOLTAGE: 250 VAC RMS
 - CURRENT RATING: 10 AMPS
 - CONTACT RESISTANCE: 16 MILLIOHMS MAX
 - INSULATOR: GENERAL PURPOSE PHENOLIC, BLACK
 - CONTACT: BRASS, MATTE TIN
 - BRACKET, DRIVE PIN: STEEL, ZINC WITH CLEAR TRIVALENT CHROMATE
- ENVIRONMENTAL:
 - OPERATING TEMPERATURE: UP TO +105°C
- TERMINATION: SOLDER

2. DIMENSIONS IN [] ARE IN MILLIMETERS
 3. ALL DIMENSIONS ARE REFERENCE

PART NUMBER	TYPE	FACTORY NUMBER
S-302H-AB	1	703 02 02 001
S-303H-AB	2	703 02 03 001
S-304H-AB	3	703 02 04 001
S-306H-AB	4	703 02 06 001

RoHS COMPLIANT

UNITS ENGLISH INCHES	PRO/VE	Cinch	
DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES FILL FINISH: 92 MAX TOLERANCES: FRACTIONS: ±.005 DECIMALS: ±.001 ANGLES: ±.001	DESIGN BY JIMENEZ	DATE 6/20/06	TITLE SOCKET ASSEMBLY, ANGLE BRACKET
DESIGN ENGINEER A. BALI	DATE 6/20/06	MATERIAL	CONTROL SPEC NUMBER 06-1067
DESIGN ENGINEERING MGR.		MATERIAL SPEC NUMBER	PROJECT NUMBER CI4789-1
MFG. ENGINEERING		CAD FILE NUMBER S302HAB	DRAWING NUMBER S-302H-AB
QUALITY ASSURANCE		CAGE IDENT NO./SIZE 71785 8	SCALE 1.000
		SHEET 1 OF 1	