



HARNESSING

SOLDERSLEEVE SHIELD TERMINATORS



✓ Active

TE CONNECTIVITY (TE)

S200-2-01-100HN

Raychem

S200-2-01-100HN

TE Internal Number: A87947-000

Alias ID: 9-1202143-1

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Product Type Shield Terminator

Operating Temperature (Max) (°C) 200

Expanded Inside Diameter (Min) 2.67 mm [.105 in]

Recovered Inside Diameter (Max) 3.68 mm [.145 in]

Pre-Installed Lead Yes

[↓ PRODUCT DRAWING](#)
English

DOCUMENTATION

Product Drawings

Solder Sleeve Shield Terminator With Pre-Installed Braid 200deg.C, RoHS Compliant

PDF

English

Catalog Pages/Data Sheets

Raychem S200 Shield Terminators

PDF

English

Product Specifications

Product Specification

Installation Procedure For Standard Solder Sleeve Shield Terminators

PDF

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type Shield Terminator

Temperature Indicator Yes

Temperature Indicator Type Fusible Ring

Splice Type Shield Terminator

Configuration Features

Pre-Installed Lead Yes

Pre-Installed Lead Type Braid

Body Features

Shield Outside Diameter (Min) 1.4 mm [.055 in]

Lead Color Braid

Lead Plating Material Nickel

Termination Features

Termination Method Solder

Dimensions

Expanded Inside Diameter (Min) 2.67 mm [.105 in]

Recovered Inside Diameter (Max) 3.68 mm [.145 in]

Overall Length 16.5 mm [.65 in]

Pre-Installed Lead Wire Size (CMA) 640

Dielectric Outside Diameter (Max) 2.67 mm [.105 in]

Jacket Outside Diameter 2.65 mm [.104 in]

Usage Conditions

Operating Temperature (Max) (°C) 200

Resistance Properties Immersion Protection

Wire Temperature (Max) (°C) 200

Industry Standards

Government Qualified No

Statement of Compliance

Statement of Compliance

PDF