

151-29500



Article Number: 151-29500

Description: Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08" - 0.52", PA66HIRHS, Black, 100/pkg

Base Data	Local Order Number	S3STM500HIRHSC2
	Type	S3STM50
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Heavy duty fir tree mount provides low insertion force and high extraction force.</li> <li>• Impact modified, heat stabilized, UV material make it ideal for heavy duty solutions</li> </ul>
	Quantity Per	bag
	Product Description	The saddle mounts act as a standoff, elevating bundles above bolt protrusions commonly found in frame rails and panels. A tension tab on the mount allows cable ties to be pre-assembled in a ready position prior to bundles being brought to the mount. The mount can secure up to four separate bundles, providing parallel spacing between the frame rail and adjacent bundles. For use with HellermannTyton T50 - T255 ties.
	Short Description	Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08" - 0.52", PA66HIRHS, Black, 100/pkg
	Product Dimensions	Length L (Imperial)
Length L (Metric)		50.0mm
Bundle Diameter 2nd Loop Max. (Imperial)		5.0"
Fixation Method		with Fir Tree (Mounts)
Width W (Imperial)		0.9"
Width W (Metric)		22.0mm
Height H (Imperial)		1.4"
Height H (Metric)		35.0mm
Height H2 (Imperial)		2.2"
Height H2 (Metric)		55.0mm
Bundle Diameter Min. (Imperial)		5.0"
Bundle Diameter Min. (Metric)		127.0mm
Bundle Diameter Max. (Imperial)		5.0"
Bundle Diameter Max. (Metric)		127.0mm

151-29500



Product Dimensions	Panel Thickness Max. (Imperial)	0.5"
	Panel Thickness Max. (Metric)	13.0mm
	Panel Thickness Min. (Imperial)	0.07"
	Panel Thickness Min. (Metric)	1.9mm
	Mounting Hole Diameter D (Imperial)	0.5"
	Mounting Hole Diameter D (Metric)	12.7 - 13.7 mm
	Bundle Diameter 1st Loop Max. (Imperial)	5.0"
	Bundle Diameter 1st Loop Max. (Metric)	127.0mm
	Mounting Hole Diameter D Max. (Metric)	13.7mm
	Mounting Hole Diameter D Min. (Metric)	12.7mm
	Bundle Diameter 2nd Loop Max. (Metric)	127.0mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL94 HB
	Minimum Extraction Force (Imperial)	200.0lbs
	Minimum Extraction Force (Metric)	890N
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987