



THE INFORMATION CONTAINED HEREIN IS CONSIDERED "PROPRIETARY" TO BEL FUSE INC. AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT THE WRITTEN APPROVAL OF BEL FUSE INC.



SCHEMATIC



ELECTRICAL CHARACTERISTICS @ 25°C

Turns Ratio 1CT : 1CT ±2%

OCL -40 TO +85 DEG C 350µH MIN. @100kHz, 100mV, WITH 8 mA DC BIAS

PIN (46-47), (43-44), (40-41), (37-38)
PIN (34-35), (31-32), (28-29), (25-26)

INSERTION LOSS

FREQ.	1MHz	65MHz	100MHz	125MHz
MAX.	1.1dB	0.5dB	0.9dB	1.5dB

RETURN LOSS 18dB MIN. @ 0.5 TO 40 MHz
MEASURED UNDER A 12-20LOG<f/80MHz>dB MIN. @ 40 TO 100MHz.
100 Ω ENVIRONMENT

COMMON TO COMMON MODE REJECTION 30dB MIN. @ 0.1 TO 100MHz.


CROSSTALK 33-20LOG<f/100MHz>dB MIN. @ 0.1 TO 100MHz.

HIPOT PER HAND-WORK-03




ORIGINATED BY	DATE	TITLE	PART NO. / DRAWING NO.	STANDARD DIM. TOL. IN INCH	[] METRIC DIM. AS REFERENCE
J.BERRY	07-26-06	DUAL 1000BASE-T	S558-5999-BQ-F	.X	UNIT : INCH [mm] REV. : PA
DRAWN BY	DATE	INDUSTRIAL TEMP	FILE NAME	.XX	SCALE : N/A SIZE : A4
J.BERRY	07-26-06		S5585999BQFPA.DWG	.XXX	PAGE : 2



THE INFORMATION CONTAINED HEREIN IS CONSIDERED "PROPRIETARY" TO BEL FUSE INC. AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT THE WRITTEN APPROVAL OF BEL FUSE INC.



SUGGESTED PCB PAD LAYOUT



NOTES:

1. STANDARD MARKING REFER TO DOC. HAND-WORK-04.
2. PACKAGE CODE: "QVS001".

ORIGINATED BY	DATE	TITLE	PART NO. / DRAWING NO.	STANDARD DIM. TOL. IN INCH	[] METRIC DIM. AS REFERENCE	
J.BERRY	07-26-06	MECHANICAL DRAWING	S558-5999-BQ-F	.X	UNIT : INCH [mm]	REV. : PA
DRAWN BY	DATE		FILE NAME	.XX ±0.01	SCALE : N/A	SIZE : A4
J.BERRY	07-26-06		S5585999BQFPA.DWG	.XXX ±0.005	SCALE : N/A	PAGE : 3



DC02(2)032305

This document is electronically generated. This is a controlled copy if used internally