

## SUMMARY

### # Wires

|         |   |
|---------|---|
| Low     | 0 |
| High    | 0 |
| Coax    | 0 |
| Triax   | 0 |
| Quad    | 0 |
| Fiber   | 0 |
| Fluidic | 0 |

### Download

[Request a quote](#)[Catalog](#)

|                  |                |
|------------------|----------------|
| Series           | SP             |
| Termination type |                |
| IP rating        | 50             |
| Cable Ø          | 4.00 - 5.20 mm |
| Matching parts   | SRN.M06.GLL.5G |

## TECHNICAL DETAILS

### Mechanics

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| Shell Style/Model | SA*: Straight plug, key (N) or keys (P, S and T), with grey cable collet |
| Keying            | 3 key (alpha=30, plug: male contacts, receptacle: female contacts)       |
| Housing Material  |                                                                          |
| Cable Fixing      | ∅ 4 - 5.2 mm                                                             |
| Variant           | G : Gray collet nut                                                      |

### Performance

|               |          |
|---------------|----------|
| Configuration |          |
| Insulator     |          |
| Rated Current | 8.5 Amps |

### Specifications

|                                                         |      |
|---------------------------------------------------------|------|
| Test voltage (kV rms) Contact-contact:                  | 1.50 |
| Air clearance min. (mm) or Creepage distance min. (mm): | 1.20 |

### Others

|            |    |
|------------|----|
| IP Rating: | 50 |
|------------|----|

---

# DRAWINGS

## Draws

## Dimensions

|     | A    | L    |
|-----|------|------|
| mm. | 16.5 | 46   |
| in. | 0,65 | 1,81 |

---

# RECOMMENDED BY LEMO

## Tools

Crimp Tool: DPC.91.701.V

## Cables