MALLORY Mallory Sonalert Products,Inc. Part #: SCE120XA3FP1B Revision: **Sales Outline Drawing Specifications:** Sound Level Category Extra Loud Mode of Operation Fast Pulse @ 10 PPS Voltage Rating 48 to 120 VAC Frequency 2900 ± 500 Hz Loudness @ 2 FT 95 to 105 dB(A) Typ. **Current Draw** 40mA MAX Housing Material 6/6 Nylon, Color: Black Storage Temperature -40° to +85° C Operating Temperature -40° to +85° C Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. Panel Mounting Knurled Nut Used to attach part to panel. The max recommended torque is 10 in-lbs. Weight (Typical) 1.6 oz (45g) NEMA 3R,4X, & 12 Approved with use of ACC03. cUL Recognition Supply voltage shall employ Transient Voltage Surge Suppression. **Options** Please contact factory. **cUL** Recognized **Dimensions:** Inches (mm) **ROHS Compliant** 1.687±.005 [42.85±.13] | MALLORY Solutions 1.210 1.240 1 1/8-24 UNS 2A THD. SOCKET (5mm Pin Spacing) KNURLED NUT -PLUGGABLE SCREW 1,313±.005 [33,34±.13] TERMINAL BLOCK .375±.005 [9,52±.13] .47±.01 [11.94±.25]-→ - .031±.005 [.79±.13] → 1,41±.1 [35,85±2.54] →

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mallory Sonalert: SCE120XA3FP1B