

SCFRX902AA Product Details



SCFRX902AA

TE Internal Number: 1-1437464-7



Active

Time Delay Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- SCF Multi-Mode, Multi-Range Timer Series
- Input Voltage = 120 VAC
- Input Voltage = 125 VDC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Series = SCF Multi-Mode, Multi-Range Timer • Termination Type = 11-Pin Octal Style Plug <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Mounting Options = Socket <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Input Voltage (VAC) = 120 • Input Voltage (VDC) = 125 • Contact Rating = 10A Resistive @ 28 VDC/120 VAC <p>Dimensions:</p> <ul style="list-style-type: none"> • Approx. Dimensions (L x W x H) (mm [in]) = 72.00 x 36.00 x 90.00 [2.836 x 1.418 x 3.546] <p>Contact Features:</p> <ul style="list-style-type: none"> • Delay Time = 0.1 seconds to 3 seconds, 0.33 seconds to 10 seconds, 0.33 minutes to 10 minutes, 0.33 hours to 10 hours, 1 minute to 30 minutes, 1 second to 30 seconds, 2 minutes to 60 minutes, 4 seconds to 120 seconds • Type of Control = Screw • Repeatability, Max. = $\pm 1\% \pm 10$ msec 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Contact - Arrangement = 2 Form C, DPDT, 2 C/O • Multiple Timing Ranges = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • Approved Standards = CE Approved, CSA Certified, UL Recognized • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not relevant for lead free process <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Range (°C) = -30 - +65 <p>Operation/Application:</p> <ul style="list-style-type: none"> • Mode of Operation = Interval, Latching Interval, Off-Delay, On-Delay <p>Other:</p> <ul style="list-style-type: none"> • Brand = Agastat • Comment = Does not include socket.