SCS230KE2

SiC Schottky Barrier Diode

V_R	1200V			
l _F	15A/30A*			
Q_{C}	51nC			
*(Per leg / Both legs)				


Features

- 1) Shorter recovery time
- 2) Reduced temperature dependence
- 3) High-speed switching possible


Construction

Silicon carbide epitaxial planer type

Outline



•Inner circuit



Packaging specifications

	Packaging	Tube	
	Reel size (mm)	-	
Type	Tape width (mm)	-	
Type	Basic ordering unit (pcs)	30	
	Packing code	С	
	Marking	SCS230KE2	

● Absolute maximum ratings (Tj = 25°C)

Parameter	Symbol	Value	Unit	
Reverse voltage (repetitive peak)	V_{RM}	1200	V	
Reverse voltage (DC)	V _R	1200	V	
Continuous forward current ^{*7}	I _F	15/30* ¹	А	
		65/130* ²	А	
Surge no repetitive forward current*7	I _{FSM}	240/480* ³	А	
		49/98* ⁴	А	
Repetitive peak forward current ^{*7}	I _{FRM}	62/120* ⁵	А	
Total power disspation*7	P _D	180/360* ⁶	W	
Junction temperature	Tj	175	°C	
Range of storage temperature	Tstg	-55 to +175	°C	

^{*1} Tc=139°C/Tc=139°C *2 PW=8.3ms sinusoidal, Tj=25°C *3 PW=10μs square, Tj=25°C

^{*4} PW=8.3ms sinusoidal, Tj=150°C *5 Tc=100°C, Tj=150°C, Duty cycle=10%

^{*6} Tc=25°C *7 Per leg / Both legs

●Electrical characteristics (Tj = 25°C) (Per leg)

Parameter	Symbol	Conditions	Values			Linit
		Conditions	Min.	Тур.	Max.	Unit
DC blocking voltage	V_{DC}	I _R =0.3mA	1200	-	-	V
Forward voltage	V _F	I _F =15A,Tj=25°C	-	1.4	1.6	V
		I _F =15A,Tj=150°C	-	1.8	-	V
		I _F =15A,Tj=175°C	-	1.9	-	V
Reverse current	I _R	V _R =1200V,Tj=25°C	-	15	300	μΑ
		V _R =1200V,Tj=150°C	-	120	-	μΑ
		V _R =1200V,Tj=175°C	-	195	-	μΑ
Total capacitance	С	V _R =1V,f=1MHz	-	790	-	pF
		V _R =800V,f=1MHz	-	63	-	pF
Total capacitive charge	Qc	V _R =800V,di/dt=500A/μs	-	51	-	nC
Switching time	tc	V _R =800V,di/dt=500A/μs	-	18	-	ns

Thermal characteristics

Parameter	Symbol	Conditions	Values			Unit
			Min.	Тур.	Max.	
Thermal resistance	R _{th(j-c)}	Per Leg	-	0.67	0.81	°C/W
		Both Legs	-	0.34	0.41	°C/W

• Electrical characteristic curves

Fig.1 V_F - I_F Characteristics (per leg)





Fig.2 V_F - I_F Characteristics (per leg)



Forward Voltage : V_F [V]

Fig.3 V_R - I_R Characteristics (per leg)





Fig.4 V_R-Ct Characteristics (per leg)



Reverse Voltage : V_R [V]

• Electrical characteristic curves

Fig.5 Thermal Resistance
vs. Pulse Width (per leg)

10


Ta=25°C
Single Pulse

0.01
0.0001 0.001 0.01 0.1 1 10 100 1000

Pulse Width: Pw [s]

Fig.6 Power Dissipation (per leg)

Fig.7 Ip-Tc Derating Curve (per leg) 80 Duty=0.1 70 Peak Forward Current : I_P [A] 60 50 Duty=0.2 40 Duty=0.5 30 20 Duty=0.8 D.C. 10 0 25 50 75 100 125 150 175 0 Case Temperature: Tc [°C]



Notes

- 1) The information contained herein is subject to change without notice.
- Before you use our Products, please contact our sales representative and verify the latest specifications:
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products specified in this document are not designed to be radiation tolerant.
- 7) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative: transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.
- 8) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 9) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 10) ROHM has used reasonable care to ensur the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 11) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 12) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 13) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/

General Precaution

- 1. Before you use our Products, you are requested to care fully read this document and fully understand its contents. ROHM shall not be in an y way responsible or liable for failure, malfunction or accident arising from the use of a ny ROHM's Products against warning, caution or note contained in this document.
- 2. All information contained in this docume nt is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sale s representative.
- 3. The information contained in this doc ument is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate an d/or error-free. ROHM shall not be in an y way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.

Notice – WE © 2015 ROHM Co., Ltd. All rights reserved. Rev.001

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ROHM Semiconductor: SCS230KE2C