

P-Channel 8-V (D-S) MOSFET

PRODUCT SUMMARY			
V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
- 8	0.040 at V _{GS} = - 4.5 V	- 4.1	7.8 nC
	0.060 at V _{GS} = - 2.5 V	- 3.4	
	0.088 at V _{GS} = - 1.8 V	- 2.0	


FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFET
- 100 % R_g Tested




APPLICATIONS

- Load Switch
- DC/DC Converter



Si2305ADS (5A)*
* Marking Code



Ordering Information: Si2305ADS-T1-E3 (Lead (Pb)-free)
Si2305ADS-T1-GE3 (Lead (Pb)-free and Halogen-free)

P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	- 8	V
Gate-Source Voltage	V _{GS}	± 8	
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	A
	T _C = 70 °C		
	T _A = 25 °C		
	T _A = 70 °C	- 3.3 ^{a, b}	
Pulsed Drain Current	I _{DM}	- 10	
Continuous Source-Drain Diode Current	T _C = 25 °C	I _S	W
	T _A = 25 °C	- 0.8 ^{a, b}	
Maximum Power Dissipation	T _C = 25 °C	P _D	W
	T _C = 70 °C	1.7	
	T _A = 25 °C	1.1	
	T _A = 70 °C	0.96 ^{a, b}	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 50 to 150	°C
Soldering Recommendations (Peak Temperature)		260	

Notes:

a. Surface Mounted on 1" x 1" FR4 board.
b. t = 10 s.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^{a, b}	$t \leq 10 \text{ s}$	R_{thJA}	100	130
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	60	75

Notes:

- a. Surface Mounted on 1" x 1" FR4 board.
- b. Maximum under Steady State conditions is 175 °C/W.







SPECIFICATIONS $T_J = 25 \text{ }^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Static							
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = - 250 \mu\text{A}$	- 8			V	
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = - 250 \mu\text{A}$		- 55		mV/°C	
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$			2.1			
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = - 250 \mu\text{A}$	- 0.45		- 0.8	V	
Gate-Source Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 8 \text{ V}$			± 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = - 8 \text{ V}, V_{GS} = 0 \text{ V}$			- 1	μA	
		$V_{DS} = - 8 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55 \text{ }^{\circ}\text{C}$			- 10		
On-State Drain Current ^a	$I_{D(on)}$	$V_{DS} \leq - 5 \text{ V}, V_{GS} = - 4.5 \text{ V}$	- 5			A	
Drain-Source On-State Resistance ^a	$R_{DS(on)}$	$V_{GS} = - 4.5 \text{ V}, I_D = - 4.1 \text{ A}$		0.032	0.040	Ω	
		$V_{GS} = - 2.5 \text{ V}, I_D = - 3.4 \text{ A}$		0.048	0.060		
		$V_{GS} = - 1.8 \text{ V}, I_D = - 2.0 \text{ A}$		0.070	0.088		
Forward Transconductance ^a	g_{fs}	$V_{DS} = - 5 \text{ V}, I_D = - 4.1 \text{ A}$		8		S	
Dynamic^b							
Input Capacitance	C_{iss}	$V_{DS} = - 4 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$		740		pF	
Output Capacitance	C_{oss}			290			
Reverse Transfer Capacitance	C_{rss}			190			
Total Gate Charge	Q_g	$V_{DS} = - 4 \text{ V}, V_{GS} = - 4.5 \text{ V}, I_D = - 4.1 \text{ A}$		7.8	15	nC	
Gate-Source Charge	Q_{gs}	$V_{DS} = - 4 \text{ V}, V_{GS} = - 2.5 \text{ V}, I_D = - 4.1 \text{ A}$		4.5	9		
Gate-Drain Charge	Q_{gd}			1.2			
Gate Resistance	R_g			1.6			
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = - 4 \text{ V}, R_L = 1.2 \Omega$ $I_D \equiv - 3.3 \text{ A}, V_{GEN} = - 4.5 \text{ V}, R_g = 1 \Omega$		1.4	7	14	Ω
Rise Time	t_r				13	20	ns
Turn-Off Delay Time	$t_{d(off)}$				35	53	
Fall Time	t_f				32	48	
Turn-On Delay Time	$t_{d(on)}$				10	20	
Rise Time	t_r	$V_{DD} = - 4 \text{ V}, R_L = 1.2 \Omega$ $I_D \equiv - 3.3 \text{ A}, V_{GEN} = - 8 \text{ V}, R_g = 1 \Omega$			5	10	ns
Turn-Off Delay Time	$t_{d(off)}$				11	17	
Fall Time	t_f				22	33	
					16	24	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25 \text{ }^{\circ}\text{C}$			- 1.4	A	
Pulse Diode Forward Current ^a	I_{SM}				- 10		
Body Diode Voltage	V_{SD}	$I_F = - 3.3 \text{ A}$		- 0.8	- 1.2	V	
Body Diode Reverse Recovery Time	t_{rr}	$I_F = - 3.3 \text{ A}, dl/dt = 100 \text{ A}/\mu\text{s}, T_J = 25 \text{ }^{\circ}\text{C}$		33	50	ns	
Body Diode Reverse Recovery Charge	Q_{rr}			14	21	nC	
Reverse Recovery Fall Time	t_a			14		ns	
Reverse Recovery Rise Time	t_b			19			






Notes:


- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2 \%$.
- b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

 T_C - Case Temperature (°C)



Current Derating*

 T_C - Case Temperature (°C)

Power, Junction-to-Case

 T_A - Ambient Temperature (°C)

Power, Junction-to-Ambient

* The power dissipation P_D is based on $T_{J(max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/pdg?69940.

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay](#):

[Si2305ADS-T1-E3](#) [SI2305ADS-T1-GE3](#)