



SMTY18AM

LOW FORWARD VOLTAGE TVS: Transky™

FEATURES AND BENEFITS

- High peak pulse power: 400W (8/20μs)
- Stand-off voltage 16V
- Low forward voltage: 0.48V @ 0.85A @ 25°C
- Low clamping factor V_{CL}/V_{BR}
- Fast response time
- Very thin package (1.0mm overall component height)

DESCRIPTION

The Transky™ is designed specifically for portable equipments and miniaturized electronics devices subject to ESD transient overvoltages.

The Transky™ combines the performance of a Transil™ or TVS (Transient Voltage Suppressor) and low forward voltage Schottky diode in a monolithic structure.

COMPLIES WITH FOLLOWING STANDARDS

IEC 61000-4-2 Level 4:

15kV (Air discharge)

8kV (Contact discharge)

MIL Standard 883E-Method 3015-7: class 3C

Human Body Model (HBM)




Table 1: Order Code

Part Number	Marking
SMTY18AM	Y18




Table 2: Absolute Ratings (limiting values)

Symbol	Parameter		Value	Unit
V_{PP}	IEC 61000-4-2 standard	Air discharge	15	kV
		Contact discharge	8	
P_{PP}	Peak pulse power dissipation (see note 1)	$T_j \text{ initial} = T_{amb}$	400	W
I_{FSM}	Non repetitive surge peak forward current	$T_p = 10 \text{ ms}$ $T_j = \text{initial} = T_{amb}$	25	A
T_{stg}	Storage temperature range		-65 to + 175	°C
T_j	Maximum operating junction temperature		150	°C

Note 1: 8/20μs pulse waveform

SMTY18AM


Table 3: Thermal Resistances

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to ambient on PCB with recommended pad layout	250	°C/W

Table 4: Static Electrical Characteristics

($T_{amb} = 25^{\circ}\text{C}$)

Symbol	Parameter
V_{BR}	Breakdown voltage
I_{RM}	Leakage current @ V_{RM}
V_{RM}	Stand-off voltage
V_{CL}	Clamping voltage
R_d	Dynamic impedance
I_{PP}	Peak pulse current
C	Capacitance



I_{RM} max @ V_{RM}		V_{CL} max @ I_{PP}		V_F max @ 0.85A	αT max	C typ @ 0V
Note 2		Note 3		Note 4		
mA	V	V	A	V	$10^{-4}/^{\circ}\text{C}$	pF
4	16	20	1	0.48	8.8	500

Note 2: $T_{amb} = 85^{\circ}\text{C}$

Note 3: 8/20 μs pulse waveform

Note 4: Pulse test $t_p = 500\mu\text{s}$, $d < 2\%$

Figure 1: Peak pulse power versus exponential pulse duration




Figure 2: Relative variation of peak pulse power versus initial junction temperature




Figure 3: Average power dissipation versus ambient temperature




Figure 4: Variation of thermal impedance junction to ambient versus pulse duration (Epoxy FR4, $e_{cu}=35\mu m$)




Figure 5: Thermal resistance junction to ambient versus copper surface under tab




Figure 6: Reverse leakage current versus junction temperature (typical values)




Figure 7: Clamping voltage versus peak pulse current (typical values)




Figure 8: Junction capacitance versus reverse voltage applied (typical values)





Figure 9: Forward voltage drop versus forward current (typical values)



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America
www.st.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[SMTY18AM](#)