


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

4			REVISIONS	0	OC. N	OC. NO. SPC-F005	DOC. NO. SPC-F005 * Effec	OC. NO. SPC-F005 * Effective: 7/8/02	OC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398
-	DCP #	REV	DESCRIPTION	DRAWN		DATE	DATE CHECKD	CHECKD DATE	CHECKD
				SHA	_	04-08-10	04-08-10 JAG		JAG





	addon's addished	

Item	Part	Material/Finish
_	Housing	Zinc Die Cast / Black Nickel (Brushed)
N	Insert Insulator	Phosphor Bronze / Gold Plated
з	Socket	Phosphor Bronze / Gold Plated
4	Cable Relief	PVP Matte Finish

Electrical Specifications:

15A # 125 VAC

5 milliohms maximum 5000 Megohms minimum # 500 VDC 1400 VAC

Contact Rating:
 Contact Resistance:
 Insulation Resistance:
 Dielectric Strength:
 Capacitance:

4pF max.

 Insertion Force:
 Withdrawal Force: 1.0 to 8.0 kg 1.0 to 8.0 kg

Mechanical Specifications:

Environmental Specifications: Operating Temperature: -55°C to 70°C

Part Number Table

SPC21448	Female XLR Plug
Part Number	Description

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS W
BELIEVE TO BE ACCUPATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LABILITY WHATSOEVER IN CONNECTION THEREWITH.

	_	_	3	₩ IT		_
	PURPOSES ONLY.		DIMENSIONS ARE	SPECIFIED,	UNLESS DTHERWISE	TOLERANCES:
	ATTROVED BY:		JAG	CHECKED BY:	SHA	DRAWN BY:
	DAIE:	7	14-08-10	DATE:	04-08-10	DATE:
SCALE:			×	J JZIS		DRAWING

	VED BY:)		ED BY:		BY:
	DAIE:	7	14-08-10	DATE:	04-08-10	DATE:
SCALE: VIS			×××	SIZE DWG. NO.	Female XLR Plug	DRAWING TITLE:
SHFFT: 1 OF			84N1227	ELECTRONIC FILE	gu	
_			D	REV		