


Cool bypass switch for photovoltaic applications

Features

- SPV1001N30 $I_F=12.5$ A, $V_R=30$ V
- SPV1001N40 $I_F=12.5$ A, $V_R=40$ V
- Very low forward voltage drop
- Very low reverse leakage current
- 150 °C operating junction temperature



Applications

- Photovoltaic panels

Description

The SPV1001N is a system-in-package solution for photovoltaic applications to perform cool bypass rectification similar to that of a conventional Schottky diode but with much lower forward voltage drop and reverse leakage current.

The device consists of a power MOSFET transistor which charges a capacitor during the OFF time, and drives its gate during the ON time using the charge previously stored in the capacitor.

The ON and OFF times are set to reduce the average voltage drop across the drain and source terminals, resulting in reduced power dissipation.

Table 1. Device summary

Order codes	Package	Packaging
SPV1001N30	PQFN 5 x 6 mm	Tape and reel
SPV1001N40		

1 Maximum ratings

1.1 Absolute maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value		Unit
		SPV1001N30	SPV1001N40	
V_R	Max DC reverse voltage	30	40	V
I_F	Max forward current	12.5	12.5	A
I_{FSM}	Non repetitive peak surge (half-wave, single phase 50-60 Hz)	250	250	A
ESD level	Human body level	$\geq 8\text{ k}$	$\geq 8\text{ k}$	V

1.2 Thermal data

Table 3. Thermal data

Symbol	Parameter	Value		Unit
T_J	Junction temperature operating range	-40 to 150	-40 to 150	°C
T_{STG}	Storage temperature range	-40 to 150	-40 to 150	°C
R_{thJC}	Thermal resistance, junction-to-case	4	4	°C/W

2 Electrical characteristics

Table 4. Electrical characteristics

Symbol	Parameter	Test conditions		SPV1001 N30			SPV1001 N40			Unit
				Min.	Typ.	Max.	Min.	Typ.	Max.	
V _{F,AVG}	AVG forward voltage drop	IF = 10A	T _J = 25°C	-	120	-	-	140	-	mV
		IF = 5A	T _J = 25°C	-	70	-	-	85	-	mV
			T _J = 125°C	-	240	-	-	280	-	mV
I _R	Reverse leakage current	VR = 30V	T _J = 25°C	-	1	-	-	1	-	µA
			T _J = 125°C	-	10	-	-	10	-	µA
D	TON/T ratio	IF = 5A	T _J = 25°C	-	95%	-	-	95%	-	-
			T _J = 125°C	-	75%	-	-	75%	-	-
V _F	Forward voltage drop	IF = 5A, T _{OFF}	T _J = 25°C	-	850	-	-	850	-	mV
			T _J = 125°C	-	600	-	-	600	-	mV
		IF = 5A, T _{ON}	T _J = 25°C	-	35	-	-	40	-	mV
			T _J = 125°C	-	135	-	-	160	-	mV

Note: For correct power dissipation and heatsink sizing, please refer to [Figure 1, 2 e 4](#)

3 Device description

A photovoltaic panel consists of a series of PV cells. In optimal conditions, all the cells are equally irradiated and function at the same current level. However, during normal operation some cells may become partially shaded or obscured. These shaded cells limit the current generated by the fully irradiated cells and, in the extreme cases where these cells are totally obscured, the current flow is blocked.

In this case the shaded cells behave like a load, and the current generated from the fully irradiated cells produces overvoltages which can reach the breakdown threshold. This phenomenon, known as a "hot spot", can cause overheating of the shaded cells and, in some cases, even permanent damage resulting in current leakage. To prevent hot spots, therefore, bypass diodes are connected in parallel to the cell strings.

The device described here has the same functionality as a Schottky diode, but with improved performance. It features very low forward voltage drop and reverse leakage current. It consists of a power MOSFET transistor which charges a capacitor during the OFF time, and drives its gate during the ON time using the charge previously stored in the capacitor. The ON and OFF times are set to reduce the average voltage drop across the drain and source terminals, resulting in reduced power dissipation.

Figure 1. Average forward power dissipation vs average forward current @ 25°C of ambient temperature




Figure 2. Average forward power dissipation vs average forward current @ 75°C of ambient temperature






Figure 3. Reverse current



1. Epoxy printed board FR4, Cu = 35 μ m

Figure 4. Thermal resistance junction-to-ambient vs copper surface under tab (1)




4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

Table 5. PQFN 5 x 6 mm mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	0.85	0.80	0.95
A1	0.02	0	0.05
D	5.00		
D2	4.26	4.16	4.36
E	6.00		
E2	2.50	2.40	2.60
e	1.27		
L	1.20	1.10	1.30
L1	0.30		
NXb	0.45		

Figure 5. PQFN 5 x 6 mm drawing



5 Revision history

Table 6. Document revision history

Date	Revision	Changes
20-Jun-2011	1	Initial release
16-Nov-2011	2	Updated <i>Figure 3</i>

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2011 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

AMEYA360

Components Supply Platform

Authorized Distribution Brand :



Website :

Welcome to visit www.ameya360.com

Contact Us :

➤ Address :

401 Building No.5, JiuGe Business Center, Lane 2301, Yishan Rd
Minhang District, Shanghai , China

➤ Sales :

Direct +86 (21) 6401-6692
Email amall@ameya360.com
QQ 800077892
Skype ameyasales1 ameyasales2

➤ Customer Service :

Email service@ameya360.com

➤ Partnership :

Tel +86 (21) 64016692-8333
Email mkt@ameya360.com