



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFAluminum, Me ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'SR-350-X'

Your search criteria matched only one product, shown below

SR-350-XY



- For Use with Stranded Aluminum or Copper Code Conductors
- Made from high strength extruded aluminum alloy to provide premium electrical and mechanical performance
 - Tin-plated to inhibit corrosion
 - Rounded bottoms to facilitate taping
 - Solid center barrier prevents contact of dissimilar metal conductors
 - Wide wire range -taking capability minimizes inventory requirements
 - UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90°C

	Part Number	SR-350-XY
	RoHS Compliancy Status	Compliant
	Note	SR-350-XY replaces SR-350-X
	Part Description	Aluminum dual rated splicer/reducer, type SR.
	Product Type	Mechanical Connectors- Splices
	CSA Certified	Yes
	UL Listed	Yes
	Height (In.)	1.19
	Height (mm)	30.2
	Length (In.)	4.19
	Length (mm)	106.4
	Width (In.)	1.13
	Width (mm)	28.7
	Aluminum or Copper Conductor Size Range	#6 AWG – 350 kcmil
	Conductor Size Range Max.	350 kcmil
	Conductor Size Range Min.	#6 AWG
	Figure No.	2
	Hex Key Size (In.)	5/16
	No. of Screws	4
	Pricing Description	Splicer/Reducer, Aluminum, Dual Rated, #6 AWG 350 kcmil
	Tightening Torque (InLbs)	275
	Min. Order UOM	PC
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.