



TE Connectivity: Every Connection Counts
© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved

+ RELAYS, CONTACTORS & SWITCHES



HALF-SIZE RELAYS



✓ Active

↓ 3D PDF

TE CONNECTIVITY (TE)

SR-7608 = M39016/40-008

SR-7608

TE Internal Number: 1617084-6

Mil-Spec: M39016/40-008

[Not EU RoHS or ELV Compliant](#)

[Find Compliant Alternatives](#)

Contact Arrangement **4 Form C, 4PDT, 4 C/O**

Input Voltage (VDC) **26.5**

Contact Current Rating (A) **2**

Coil Voltage Rating (VDC) **26.5**

Coil Resistance (Ω) **390**

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IJS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[RELAY](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Coil Latching **Without**

Product Type **Relay**

MOSFET Driver **Without**

Relay Type **Military/Aerospace High Performance**

Enclosure Type **Hermetically Sealed**

Configuration Features Transistor Driver **Without**

Electrical Characteristics

Input Voltage (VDC)	26.5
Coil Voltage Rating (VDC)	26.5
Coil Resistance (Ω)	390
Coil Power Rating (DC) (mW)	1801
Coil Suppression Diode	Without
Actuating System	DC
Vibration	15G's, 10 – 2000Hz
Coil Magnetic System	Non-Polarized, Monostable
Coil Power Measurement	Milliwatts
Coil Polarity Protection Diode	Without
Shock	100G's, 6ms

Contact Features

Contact Arrangement	4 Form C, 4PDT, 4 C/O
Contact Current Rating (A)	2

Termination Features Termination Type **PC Pins**

Mechanical Attachment Mounting Type **Plain Case**

Usage Conditions Operating Temperature Range (°C) **-65 – 125**

Product Compliance [Statement of Compliance](#)
PDF
[VIEW ALL PRODUCT COMPLIANCE](#)