



SCHOTTKY BARRIER RECTIFIER

SR5020P THRU SR5060P

VOLTAGE RANGE

20 to 60 Volts

CURRENT


50.0 Amperes

FEATURES

- Plastic package has Underwriters Laboratory Flammability classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low forward voltage, high current capability
- High surge capacity
- For use in low voltage, high frequency inverters. Free wheeling, and polarity protection applications

MECHANICAL DATA

- Case: TO-3P molded Plastic
- Terminals: Lead solderable per MIL-STD-202, Method 208
- Polarity: as marked
- Mounting position: Any
- Weight: 0.2ounce, 5.6 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	SR 5020P	SR 5030P	SR 5035P	SR 5040P	SR 5045P	SR 5050P	SR 5060P	SR 5080P	SR50 100P	SR50 150P	SR50 200P	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum RMS Voltage		V _{RMS}	14	21	25	28	32	35	42	56	70	105	140	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum Average Forward Rectified Current At Tc=90℃		I _(AV)	50.0											Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)		I _{FSM}	400											Amps
Maximum Forward Voltage at 25.0A per element		V _F	0.65			0.72			0.75			0.85		Volts
Maximum DC Reverse Current at rated DC Blocking Voltage per element	T _C = 50℃	I _R	2.0											mA
	T _C = 100℃		100											
Typical Junction Capacitance(Note2)		C _j	700											pF
Typical Thermal Resistance (Note 1)		R _{θJC}	0.8											℃/W
Operating Storage Temperature Range		T _J T _{STG}	(-55 to +150)											℃

Notes:

- Thermal Resistance Junction to Ambient
- Measured at $V_R=4\text{v}$ and $f=1\text{MHz}$



SCHOTTKY BARRIER RECTIFIER

SR5020P THRU SR5060P

VOLTAGE RANGE 20 to 60 Volts
CURRENT 50.0 Ampere

RATINGS AND CHARACTERISTIC CURVES SR5020P THRU SR50200P

FIG.1-FORWARD CURRENT
DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE
SURGE CURRENT




FIG.3-TYPICAL REVERSE
CHARACTERISTICS




FIG.4-TYPICAL FORWARD
CHARACTERISTICS




FIG.5-TYPICAL JUNCTIONCAPACITANCE

