

SS495B - SP

SS490 Series Cost - Reduced Miniature Ratiometric Linear Hall - Effect Sensor; surface mount; available in 1,000 per tape and reel

Features

- ? Small size
- ? Low power consumption
- ? Single current sinking or current sourcing output
- ? Linear output for circuit design flexibility
- ? Built - in thin - film resistors - laser trimmed for precise sensitivity and temperature compensation
- ? Rail- to - rail operation provides more useable signal for higher accuracy
- ? Responds to either positive or negative gauss
- ? Quad Hall sensing element for stable output

Representative photograph, actual product appearance may vary.

Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.

Description

The SS490 Series MRL (Miniature Ratiometric Linear) sensors are versatile linear Hall effect devices operated by the magnetic field from a permanent magnet or an electromagnet. The ratiometric output voltage is set by the supply voltage. It varies in proportion to the strength of the magnetic field.

The integrated circuitry provides increased temperature stability and sensitivity. Laser trimmed thin film resistors on the chip provide high accuracy (null to ± 3%, sensitivity up to ±3%) and temperature compensation. The positive temperature coefficient of the sensitivity (+0.02 %/°C typical) compensates for the negative temperature coefficients of low cost magnets.

The SS490B Series sensors offer cost - effective MRL sensing with slightly wider specifications than the SS490 products. The SS490B has a typical sinking or sourcing output of 1.5 mA continuous, uses seven mA of supply current at 5.0 volts at 25° C, for predictable performance over the full temperature range. SS490B Series sensors have wider null and sensitivity tolerances and a wider drift over temperature.

NOTE: Products ordered in bulk packaging (plastic bags) may not have perfectly straight leads as a result of normal handling and shipping operations. Please order tape packaging option for applications with critical lead straightness requirements.

SS495B - SP

SS490 Series Cost - Reduced Miniature Ratiometric Linear Hall - Effect Sensor; surface mount; available in 1,000 per tape and reel

Product Specifications	
Product Type	Miniature Hall - Effect Linear Position Sensor
Package Quantity/Type	Available in 1,000/Tape and Reel
Package Style	Surface Mount
Supply Voltage	4.5 Vdc to 10.5 Vdc
Output Type	Sink/Source
Magnetic Actuation Type	Ratiometric
Operating Temperature Range	- 40 °C to 150 °C [- 40 °F to 302 °F]
Output Voltage	0.2 Vdc to (V _s - 0.2 Vdc) typ., 0.4 Vdc to (V _s - 0.4 Vdc) min.
Linearity (% of Span)	- 1.0 % typ., - 1.5 % max.
Output Voltage Span (min.)	0.4 Vdc to (V _s - 0.4 Vdc)
Availability	Global
Supply Current (max. @ 25 °C)	8.7 mA @ 5 Vdc
Sensitivity @ 25 °C	3.125 mV ± 0.250 mV/G
Output Voltage Swing (Negative G)	0.4 Vdc
Output Voltage Swing (Positive G)	V _s - 0.4 Vdc
Temperature Error (@ 25 °C) Null Shift (%/°C)	- 0.08 % min., 0.08 % max.
Temperature Error (@ 25 °C) Sensitivity (%/°C)	- 0.02 % min., 0.08 % max.
Output Current Typical Source (V _s > 4.5 Vdc)	1.5 mA
Output Current Minimum Source (V _s > 4.5 Vdc)	1 mA
Output Current Minimum Sink (V _s > 4.5 Vdc)	0.6 mA
Output Current Minimum Sink (V _s > 5.0 Vdc)	1 mA
Magnetic Range (typ.)	- 67 mT to 67 mT [- 670 G to 670 G]
Magnetic Range (min.)	- 60 mT to 60 mT [- 600 G to 600 G]
Output Voltage Span (typ.)	0.2 Vdc to (V _s - 0.2 Vdc)
Null (Output @ 0 G)	2.50 Vdc ± 0.150 Vdc
Response Time (μ s)	3 μ s
Series Name	SS490 Series

SS495B - SP

SS490 Series Cost - Reduced Miniature Ratiometric Linear Hall - Effect Sensor; surface mount; available in 1,000 per tape and reel

SS495B - SP

SS490 Series Cost - Reduced Miniature Ratiometric Linear Hall - Effect Sensor; surface mount; available in 1,000 per tape and reel

SS495B - SP

**WARNING**

PERSONAL INJURY
DO NOT USE these products as safety or emergency stop devices, or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

**WARNING**

MISUSE OF DOCUMENTATION

- ? The information presented in this product sheet (or catalog) is for reference only. DO NOT USE this document as product installation information.
- ? Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.