


24-Outlet Power Strip with Industrial Surge Protector, 15-ft. Cord, 450 Joules, 72 in. length

MODEL NUMBER: SS7619-15



Description

The SS7619-15 6-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting

Highlights

- 24 outlets
- 15-ft. cord
- 72-in. length
- 450-joule rating

Applications

Offers outlet power distribution
with surge suppression for
multiple loads in equipment
racks, computer rooms,
workbenches and raceways in a
variety of internetworking,
telecommunications, audio/video
and live sound applications.

Package Includes

- SS7619-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 24 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 6-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

Features

- Long 6-ft./72-in. strip offers convenient power distribution and surge suppression in equipment racks, computer rooms, workbenches, raceways and more
- Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff with integrated 15 amp circuit breaker
- Adjustable mounting clips support installation in a variety of applications
- UL1363/1449 400V (USA), cUL (Canada)
- 15A power handling capacity with circuit breaker
- 450-joule AC surge suppression
- 15-ft. AC line cord

Specifications



ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(24) 5-15R	
Output (Watts)	1800	
Circuit Breaker (amps)	15A	
Outlet Type	NEMA 5-15R	
Outlet Spacing	2.795-in. (center to center)	
USB Charging	No	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input Connection Type	NEMA 5-15P	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.6	
Input Cord Gauge Type	14 gauge, SJT	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	22000	
USER INTERFACE, ALERTS & CON	TROLS	
Switches	Combination AC circuit breaker and lighted two-position power switch controls power to all outlets	
Locking Switch Cover	Transparent locking switch cover prevents accidental shutoff	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	450	
UL1449 Let Through Rating	400V UL Verified	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (hwd / in.)	72 x 1.5 x 1.5	
Unit Dimensions (hwd / cm)	182.9 x 3.8 x 3.8	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Material of Construction	Metal	
Included Mounting Accessories	Set of adjustable mounting clamps	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Outlets Measurement (Center to Center)	69mm	
Metal Case	Yes	
SPECIAL FEATURES		
Right-Angle Plug	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.