

[Home](#) > [Products](#) > [By Type](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

SSFR90B Product Details



Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- SSF Universal Timer Series
- Input Voltage = 240 VAC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC
- Mounting Options = DIN Rail, Machine Tool Track Mounting, Surface

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

SSFR90B
(1423167-3)
TE Internal Number: 1423167-3

 [Active](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: • None Available Catalog Pages/Data Sheets: • None Available Product Specifications: • None Available Application Specifications: • None Available Instruction Sheets: • None Available CAD Files: • None Available	Additional Information: • Product Line Information Related Products: • Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: • Termination Type = Screw Terminal Electrical Characteristics: • Input Voltage (VAC) = 240 • Contact Rating = 10A Resistive @ 28 VDC/120 VAC Body Related Features: • Series = SSF Universal Timer Contact Related Features: • Mounting Options = DIN Rail, Machine Tool Track Mounting, Surface • Mode of Operation = Interval, Latching Interval, Off-Delay, On-Delay • Delay Time = 0.1 seconds to 3 seconds, 0.33 seconds to 10 seconds, 0.33 minutes to 10 minutes, 0.33 hours to 10 hours, 1 minute to 30 minutes, 1 second to 30 seconds, 2 minutes to 60 minutes, 4 seconds to 120 seconds • Type of Control = Screw • Repeatability, Max. = ±1% ±10 msec • Approved Standards = CE Approved, CSA Certified, UL Recognized • Approx. Dimensions (L x W x H) (mm [in]) = 56.00 x 68.00 x 97.00 [2.206 x 2.679 x 3.821]	Configuration Related Features: • Contact Arrangement = 2 Form C, DPDT, 2 C/O • Multiple Timing Ranges = Without Industry Standards: • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not suitable for lead free processing Conditions for Usage: • Temperature Range (?C) = -30 - +65 Other: • Brand = Agastat

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)