

# Corded UPS Backplate Outlet Kit for SU6000RT3UHV UPS, 200/208/240V Input/Output, NEMA L6-30R

MODEL NUMBER: SUPDM11



#### **Highlights**

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system from hardware in/out to one with an AC plug and outlets
- 10 ft. / 3m AC input cord with NEMA L6-30P plug
- 2 NEMA L6-30R output receptacle
- Easy quick-connect wiring installs in minutes

### **Description**

Tripp Lite's SUPDM11 corded backplate kit converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet. 10 ft./3m input line cord with L6-30P plug enables connection to 200/208/240V 30A mains power. Two L6-30R output receptacles allow for the connection of high current equipment load or power distribution units(PDU). Easy quick-connect wiring installs in minutes.

#### **Features**

- Converts Tripp Lite's hardwire SU6000RT3UHV UPS system to one with an AC plug and outlet
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Two L6-30R output receptacles pass 200/208/240V output voltage on to connected equipment
- Easy quick-connect wiring installs in minutes

## **Specifications**

OVERVIEW		
Accessories Type	Backplate Outlet Kit	
ОШТРИТ		
Output Receptacles	(1) L6-30R	
Output Nominal Voltage	200/208/240V	
INPUT		
UPS Input Cord Length (ft.)	10	





UPS Input Cord Length (m)         3.05           Recommended Electrical Service         30A 200/208/240V           Input Connection Type         NEMA L6-30P           PHYSICAL           Shipping Dimensions (hwd / in.)         5.5 x 9 x 14.25           Shipping Dimensions (hwd / cm)         14 x 22.9 x 36.2           Shipping Weight (lbs.)         4.7           Shipping Weight (kg)         2.2           Unit Dimensions (hwd / cm)         3 x 3.75 x 4.75           Unit Weight (lbs.)         4           Unit Weight (kg)         1.8           Material of Construction         Steel           WARRANTY           Product Warranty Period (Worldwide)         2-year limited warranty			
Input Connection Type  NEMA L6-30P  PHYSICAL  Shipping Dimensions (hwd / in.) 5.5 x 9 x 14.25  Shipping Dimensions (hwd / cm) 14 x 22.9 x 36.2  Shipping Weight (lbs.) 4.7  Shipping Weight (kg) 2.2  Unit Dimensions (hwd / cm) 3 x 3.75 x 4.75  Unit Dimensions (hwd / cm) 7.6 x 9.5 x 12.1  Unit Weight (lbs.) 4  Unit Weight (kg) 1.8  Material of Construction Steel	UPS Input Cord Length (m)	3.05	
PHYSICAL  Shipping Dimensions (hwd / in.) 5.5 x 9 x 14.25  Shipping Dimensions (hwd / cm) 14 x 22.9 x 36.2  Shipping Weight (lbs.) 4.7  Shipping Weight (kg) 2.2  Unit Dimensions (hwd / in.) 3 x 3.75 x 4.75  Unit Dimensions (hwd / cm) 7.6 x 9.5 x 12.1  Unit Weight (lbs.) 4  Unit Weight (kg) 1.8  Material of Construction Steel	Recommended Electrical Service	30A 200/208/240V	
Shipping Dimensions (hwd / in.) 5.5 x 9 x 14.25 Shipping Dimensions (hwd / cm) 14 x 22.9 x 36.2 Shipping Weight (lbs.) 4.7 Shipping Weight (kg) 2.2 Unit Dimensions (hwd / in.) 3 x 3.75 x 4.75 Unit Dimensions (hwd / cm) 7.6 x 9.5 x 12.1 Unit Weight (lbs.) 4 Unit Weight (kg) 1.8 Material of Construction Steel	Input Connection Type	NEMA L6-30P	
Shipping Dimensions (hwd / cm) 14 x 22.9 x 36.2  Shipping Weight (lbs.) 4.7  Shipping Weight (kg) 2.2  Unit Dimensions (hwd / in.) 3 x 3.75 x 4.75  Unit Dimensions (hwd / cm) 7.6 x 9.5 x 12.1  Unit Weight (lbs.) 4  Unit Weight (kg) 1.8  Material of Construction Steel	PHYSICAL		
Shipping Weight (lbs.)  4.7  Shipping Weight (kg)  2.2  Unit Dimensions (hwd / in.)  3 x 3.75 x 4.75  Unit Dimensions (hwd / cm)  7.6 x 9.5 x 12.1  Unit Weight (lbs.)  4  Unit Weight (kg)  1.8  Material of Construction  Steel	Shipping Dimensions (hwd / in.)	5.5 x 9 x 14.25	
Shipping Weight (kg)  2.2  Unit Dimensions (hwd / in.)  3 x 3.75 x 4.75  Unit Dimensions (hwd / cm)  7.6 x 9.5 x 12.1  Unit Weight (lbs.)  4  Unit Weight (kg)  1.8  Material of Construction  Steel	Shipping Dimensions (hwd / cm)	14 x 22.9 x 36.2	
Unit Dimensions (hwd / in.)  3 x 3.75 x 4.75  Unit Dimensions (hwd / cm)  7.6 x 9.5 x 12.1  Unit Weight (lbs.)  4  Unit Weight (kg)  1.8  Material of Construction  Steel  WARRANTY	Shipping Weight (lbs.)	4.7	
Unit Dimensions (hwd / cm) 7.6 x 9.5 x 12.1  Unit Weight (lbs.) 4  Unit Weight (kg) 1.8  Material of Construction Steel	Shipping Weight (kg)	2.2	
Unit Weight (lbs.) 4 Unit Weight (kg) 1.8 Material of Construction Steel	Unit Dimensions (hwd / in.)	3 x 3.75 x 4.75	
Unit Weight (kg) 1.8  Material of Construction Steel  WARRANTY	Unit Dimensions (hwd / cm)	7.6 x 9.5 x 12.1	
Material of Construction Steel  WARRANTY	Unit Weight (lbs.)	4	
WARRANTY	Unit Weight (kg)	1.8	
	Material of Construction	Steel	
Product Warranty Period (Worldwide) 2-year limited warranty	WARRANTY		
	Product Warranty Period (Worldwide)	2-year limited warranty	

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies