

208/240V Single Phase Whip in 35-ft length with L6-30R for Breakered 3 Phase Distribution Cabinets

MODEL NUMBER: **SUWL630C-35**



Highlights

- 208/240V single phase whip distribution cabinet accessory
- 35 ft. length with 3 ft. removed outer jacket
- 3 conductor 10AWG stranded wire
- L6-30R outlet (208/240V 30A)

Description

208/240V single phase whip with L6-30R outlet distributes power from 3 phase distribution cabinet to critical equipment racks. 35 ft. insulated and 3 ft. of removed outer jacket cabling supports hardwire connection to [SUBB230](#) circuit breaker in SUDC208V series 3 phase distribution racks. L6-30R outlet is compatible with 208/240V loads and Power Distribution Units(PDUs) supporting a L6-30P plug-in connection.

Features

- 208/240V single phase whip with L6-30R outlet
- Distributes power from 3 phase distribution cabinet to critical equipment racks
- 35 ft. insulated and 3 ft. of removed outer jacket cabling supports hardwire connection to [SUBB230](#) circuit breaker in SUDC208V series 3 phase distribution racks
- L6-30R outlet is compatible with 208/240V loads and Power Distribution Units(PDUs) supporting a L6-30P plug-in connection

Specifications

OVERVIEW	
Accessories Type	Single-Phase Whip Cable
OUTPUT	
Output Receptacles	(1) L6-30R
PDU Recommendation Notes	Compatible with all PDU brands fitted with a L6-30P(30A 208/240V) input plug, including Tripp Lite PDU1230 , PDUV30HV , PDUMH30HV , PDUMV30HV , PDUMNH30 , PDUMNV30 , PDUMH30HV19NET , PDUMH30HVNET and PDUMV30HVNET
INPUT	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Input Connection Type	Hardwire (3 wire - L, N, G)
Cable Length (ft.)	35
Cable Length (m)	10.67
PHYSICAL	
Shipping Weight (lbs.)	12.9
Shipping Weight (kg)	5.9
Color	Black
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>