

AULT SPECIFICATIONS

SW201 and SW301 Universal Series

Final 3/31/97

INPUT

Voltage	100-250 VAC - 10%, +6%
Line Frequency	47-63 Hz
Current	0.65A Max. at 90 VAC input
Protection	Internal primary current fuse Inrush limiting
Configuration	In Case IEC320 with Ground

OUTPUT

<i>Model</i>	<i>Voltage</i>	<i>Min. Current</i>	<i>Max. Current</i>	<i>Max. Watts</i>	<i>Max. Power</i>
SW201KA0012F01	+5VDC	0A	4.0A	20.0W	22.5
	+12VDC	0A	1.0A	12.0W	
SW301KA0012F01	+5VDC	0A	4.0A	20.0W	22.5
	+12VDC	0A	1.0A	12.0W	
	-12VDC	0A	0.6A	7.2W	

Combined Line and Load Voltage Regulation Excluding Cord Ripple

+5: $\pm 1\%$ combined +5, +12 output of >0.6A
+12: $\pm 5\%$ combined +5, +12 output of 0.6A
-12: $\pm 6\%$ combined +5, +12 output of >0.6A
+5: 50 mV p-p Max., for combined +5, +12 output >0.6A
+12: 100 mV p-p Max., for combined +5, +12 output >0.6A
-12: 100 mV p-p Max., for combined +5, +12, output.>0.6A

Transient Response Holdup Time Protection

0.5 msec for 50% load change typical
18 msec @ 120VAC; 100 msec @ 240VAC
Foldback overcurrent protection on all outputs
Short circuit protection on all outputs
Optional overvoltage crowbar 6.8V Max. on +5
Optional reverse polarity crowbar on -12

Cord and Connectors

6 ft., 4 or 5 Conductor, 18 AWG, Ault #12 Connector
Other Connectors are also available

ELECTRICAL

Topology Dielectric Withstand

Switching - Variable Frequency Flyback
3000 VAC, 4250 VDC primary-secondary
1500 VAC, 2150 VDC primary-ground
500 VDC secondary-ground

Spacing Leakage Current Efficiency

8mm primary-secondary
Less than 0.75 mA at 265 VAC 50 Hz
Up to 72%

EMI CE

Complies with EMC Directives
CE Compliant

SAFETY APPROVALS

UL1950, CSA950, TUV/IEC950

ENVIRONMENTAL

Operating Temperature Storage Temperature Relative Humidity Altitude Cooling

0° to 50° C with no derating
-30°C to +85° C
5% to 95% non-condensing
0 - 10,000 feet
Convectional non-vented case

MECHANICAL


Case and Dimensions

LP7 - Desktop
5.08 L x 3.05 W x 1.59 H (in)
129 L x 77 W X 40 H (mm)
Case Material
Black 94V0 Polycarbonate
Weight
13 ounces, 370 grams (excluding cords)

WARRANTY

3 Years

LEADWIRE HOOK-UP		
PIN #	COLOR	FUNCTION
1	BLACK	COMMON
2	GREEN	GROUND
3	BROWN	+5 VDC
4	WHITE	-12 VDC
5	RED	+12 VDC



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SL Power:

[SW201MA0012F01](#) [SW301MA0012F01](#) [SW201KA0012F01](#) [SW301KA0012F01](#)