

111-15206

HellermannTyton



Article Number: 111-15206

Description: Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg

Base Data		
	Local Order Number	T150R0UVX2
	Type	T150R(U)
	Color	Black (BK)
	Features and benefits	• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Head design provides high tensile strength with very low insertion force.
	Quantity Per	bag
	Brand Family	T-Series
	Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	GLOBAL PART NAME	T150R(U)-PA66UV-BK
	Short Description	Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66UV, Black, 25/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	175.0lbs
	Minimum Tensile Strength (Metric)	780.0N
	Length L (Imperial)	15.4"
	Length L (Metric)	390.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Variant	Inside Serrated
	Width W (Imperial)	0.35"
	Width W (Metric)	8.9mm
	Bundle Diameter Min. (Imperial)	0.32"
	Bundle Diameter Min. (Metric)	8.0mm

111-15206

HellermannTyton

Product Dimensions	Bundle Diameter Max. (Imperial)	4.1"
	Bundle Diameter Max. (Metric)	104.1mm
	Thickness T (Imperial)	0.075"
	Thickness T (Metric)	1.9mm
Material and Specifications		
	Material	Polyamide 6.6 UV-resistant (PA66UV)
	Material Shortcut	PA66UV
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987