

805-0989 T30R0UVC2

Cable Tie, 30lb, 5.9", Max Bun Dia. 1.38", PA66UV Stabilized, Black, 100/pk

Article Number: 112-03060

Part Number: T30R0UVC2

Type: T30R



Base Data

Part No.	T30R0UVC2
Type	T30R
Color	Black
Features	HellermannTyton offers cable ties made of PA66UV stabilized material. This provides additional protection against UV radiation for long term outdoor use and is available in various tensile strengths and bundle diameters.
Application	Used to bundle and secure wire and cable.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No

Tie Closure plastic pawl

Variant Inside Serrated

Product Dimensions

Min. Tensile Strength 30 lbs / 135 N

Length (L) 5.9 " / 150 mm

Width (W) .14 " / 3.5 mm

Min. Ø Bundle .06 " / 1.5 mm

Max. Ø Bundle 1.38 " / 35.0 mm

Thickness 1.2 mm

Material and Specifications

Material Polyamide 6.6 UV-stabilized (PA66UV)

Certification MIL 53421 / UL ZODZ2.E64139

CSA Certified No

Flammability UL94 V2

Material Specification HF / RoHS

Operating Temperature -40 °C to +85 °C, intermittent +105 °C (for 500 h)

ROHS Conformity  RoHS