

111-00439

HellermannTyton



Article Number: 111-00439

Description: Standard Cable Tie, 5.8" Long, 30lb Tensile Strength, PA66UV, Black, 1000/pkg

Base Data		
	Local Order Number	T30R0UVM4
	Type	T30R
	Color	Black (BK)
	Features and Benefits	• UV stabilized cable ties contain an inhibitor that prolongs the life of the tie in UV exposures. • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations to provide a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Standard Cable Tie, 5.8" Long, 30lb Tensile Strength, PA66UV, Black, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	30.0lbs
	Minimum Tensile Strength (Metric)	135.0N
	Length L (Imperial)	5.8"
	Length L (Metric)	148.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.14"
	Width W (Metric)	3.6mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm

111-00439

HellermannTyton

Product Dimensions	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Thickness T (Metric)	1.1mm
Material and Specifications		
	Material	Polyamide 6.6 UV-resistant (PA66UV)
	Material Shortcut	PA66UV
	US MILSPEC	MS3367-5-0
	Flammability	UL94 HB
	Halogenfree	Yes
	ROHS Compliant	Yes
	Certification/Specification	Cage Code 53421
Logistic and Packaging		
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987