

**GROUP F – 316 SS****316 STAINLESS STEEL****ENCAPSULATED TRANSFORMERS, 115° C RISE****480 DELTA PRIMARY VOLTS — 208Y/120 SECONDARY VOLTS — 3Ø, 60 Hz**

| KVA  | CATALOG NO. | APPROX. DIMENSIONS<br>Inches (Cm.) |              |              | APPROX.<br>SHIP WEIGHT<br>Lbs. (Kg.) | TYPE MTG.<br>W – Wall<br>F – Floor | KNOCKOUTS<br>Inches (Cm.) | WEATHER<br>SHIELD<br>P/N | Wiring Diagrams &<br>Design Figures<br>Begin on Page 154 |
|------|-------------|------------------------------------|--------------|--------------|--------------------------------------|------------------------------------|---------------------------|--------------------------|----------------------------------------------------------|
|      |             | HEIGHT                             | WIDTH        | DEPTH        |                                      |                                    |                           |                          |                                                          |
| 3.0  | T2A53308SS  | 10.38 (26.4)                       | 12.37 (31.4) | 7.47 (19.0)  | 75 (34.0)                            | W                                  | NA                        | NA                       | 21-F                                                     |
| 6.0  | T2A53309SS  | 11.83 (30.0)                       | 14.17 (36.0) | 8.82 (22.4)  | 140 (63.5)                           | W                                  | NA                        | NA                       | 21-F                                                     |
| 9.0  | T2A53310SS  | 14.03 (35.6)                       | 17.77 (45.1) | 11.52 (29.3) | 180 (81.6)                           | W                                  | NA                        | NA                       | 21-F                                                     |
| 15.0 | T353311SS   | 18.86 (47.9)                       | 20.30 (51.6) | 9.03 (22.9)  | 250 (113.0)                          | F                                  | NA                        | NA                       | 21-I                                                     |
| 30.0 | T379312SS   | 24.81 (63.0)                       | 27.13 (68.9) | 11.14 (28.3) | 613 (278.1)                          | F                                  | NA                        | NA                       | 22-I                                                     |
| 45.0 | T379313SS   | 25.31 (64.3)                       | 30.18 (76.7) | 12.76 (32.4) | 780 (354.0)                          | F                                  | NA                        | NA                       | 22-I                                                     |
| 75.0 | T379314SS   | 26.82 (68.1)                       | 34.68 (88.1) | 15.25 (38.7) | 1126 (511.0)                         | F                                  | NA                        | NA                       | 22-I                                                     |

Notes: 3.0 through 75.0 kVA units encapsulated (TP1 exempt)

**GROUP G****480 DELTA PRIMARY VOLTS — 240 DELTA / 120 TAP SECONDARY VOLTS****MAY BE USED ON A 4 WIRE 480Y/277 VOLT SUPPLY — 3Ø, 60 Hz**

| KVA <sup>①</sup> | CATALOG NO. | APPROX. DIMENSIONS<br>Inches (Cm.) |               |               | APPROX.<br>SHIP WEIGHT<br>Lbs. (Kg.) | TYPE MTG.<br>W – Wall<br>F – Floor | KNOCKOUTS<br>Inches (Cm.) | WEATHER<br>SHIELD<br>P/N | Wiring Diagrams &<br>Design Figures<br>Begin on Page 154 |
|------------------|-------------|------------------------------------|---------------|---------------|--------------------------------------|------------------------------------|---------------------------|--------------------------|----------------------------------------------------------|
|                  |             | HEIGHT                             | WIDTH         | DEPTH         |                                      |                                    |                           |                          |                                                          |
| 3.0              | T2A-533281S | 10.38 (26.4)                       | 12.37 (31.4)  | 7.47 (19.0)   | 75 (34.0)                            | W                                  | 0.75-1.25 (1.9-3.2)       | NA                       | 25-F                                                     |
| 6.0              | T2A-533291S | 11.83 (30.0)                       | 14.17 (36.0)  | 8.82 (22.4)   | 140 (63.5)                           | W                                  | 0.75-1.25 (1.9-3.2)       | NA                       | 25-F                                                     |
| 9.0              | T2A-533401S | 14.03 (36.0)                       | 17.77 (45.1)  | 11.52 (29.3)  | 180 (81.6)                           | W                                  | 0.75-1.25 (1.9-3.2)       | NA                       | 25-F                                                     |
| 15.0             | T3-533411S  | 18.86 (47.9)                       | 20.30 (51.6)  | 9.03 (22.9)   | 250 (113.0)                          | F ①                                | NA                        | NA                       | 25-I                                                     |
| 30.0             | TP1533423S  | 25.50 (64.8)                       | 24.39 (61.9)  | 19.37 (49.2)  | 325 (147.0)                          | F ①                                | NA                        | WSA1                     | 26-E                                                     |
| 45.0             | TP1533433S  | 25.50 (64.8)                       | 24.39 (61.9)  | 19.37 (49.2)  | 400 (181.0)                          | F ①                                | NA                        | WSA1                     | 26-E                                                     |
| 75.0             | TP1533443S  | 29.41 (74.7)                       | 28.15 (71.5)  | 22.37 (56.8)  | 500 (226.8)                          | F ①                                | NA                        | WSA2                     | 26-E                                                     |
| 112.5            | TP1533453S  | 35.47 (91.2)                       | 31.90 (81.0)  | 26.88 (68.3)  | 750 (340.0)                          | F                                  | NA                        | WSA3                     | 26-E                                                     |
| 150.0            | TP1533463S  | 41.52 (105.5)                      | 32.90 (83.6)  | 29.87 (75.9)  | 1125 (510.0)                         | F                                  | NA                        | WSA4                     | 26-E                                                     |
| 225.0            | TP1533473S  | 41.52 (105.5)                      | 32.90 (83.6)  | 29.87 (75.9)  | 1200 (544.0)                         | F                                  | NA                        | WSA4                     | 26-E                                                     |
| 300.0            | TP1533483S  | 45.60 (115.8)                      | 39.50 (100.3) | 35.50 (90.2)  | 1550 (703.0)                         | F                                  | NA                        | WSA5                     | 26-G                                                     |
| 500.0            | TP1533493S  | 62.00 (157.5)                      | 54.00 (137.2) | 42.00 (106.7) | 2675 (1213.0)                        | F                                  | NA                        | WSA7                     | 26-G                                                     |
| 750.0            | TP1533503S  | 62.80 (159.5)                      | 54.00 (137.2) | 41.50 (105.4) | 3408 (1545.8)                        | F                                  | NA                        | WSA6                     | 26-G                                                     |

Notes: 3.0 through 15.0 kVA units encapsulated (TP1 exempt), 30.0 through 750.0 kVA TP1 compliant. 3.0 kVA through 750.0 kVA provided with 120V lighting tap limited to 5% of nameplate rating.

**GROUP G2****LOW NOISE (minus 3 db)****480 DELTA PRIMARY VOLTS — 240 DELTA / 120 TAP SECONDARY VOLTS****MAY BE USED ON A 4 WIRE 480Y/277 VOLT SUPPLY — 3Ø, 60 Hz**

| KVA   | CATALOG NO. | APPROX. DIMENSIONS<br>Inches (Cm.) |              |              | APPROX.<br>SHIP WEIGHT<br>Lbs. (Kg.) | TYPE MTG.<br>W – Wall<br>F – Floor | KNOCKOUTS<br>Inches (Cm.) | WEATHER<br>SHIELD<br>P/N | Wiring Diagrams &<br>Design Figures<br>Begin on Page 154 |
|-------|-------------|------------------------------------|--------------|--------------|--------------------------------------|------------------------------------|---------------------------|--------------------------|----------------------------------------------------------|
|       |             | HEIGHT                             | WIDTH        | DEPTH        |                                      |                                    |                           |                          |                                                          |
| 30.0  | LN3533423S  | 29.48 (74.9)                       | 28.15 (71.5) | 22.37 (56.8) | 360 (163.3)                          | F ①                                | NA                        | WSA2                     | 26-E                                                     |
| 45.0  | LN3533433S  | 29.48 (74.9)                       | 28.15 (71.5) | 22.37 (56.8) | 417 (189.2)                          | F ①                                | NA                        | WSA2                     | 26-E                                                     |
| 75.0  | LN3533443S  | 35.47 (90.1)                       | 31.90 (81.0) | 26.88 (68.3) | 536 (243.1)                          | F ①                                | NA                        | WSA3                     | 26-E                                                     |
| 112.5 | LN3533453S  | 41.50 (105.4)                      | 32.90 (83.6) | 29.90 (75.9) | 800 (362.9)                          | F                                  | NA                        | WSA4                     | 26-E                                                     |
| 150.0 | LN3533463S  | 41.50 (105.4)                      | 32.90 (83.6) | 29.90 (75.9) | 950 (430.9)                          | F                                  | NA                        | WSA4                     | 26-E                                                     |
| 225.0 | LN3533473S  | 41.50 (105.4)                      | 32.90 (83.6) | 29.90 (75.9) | 1256 (569.7)                         | F                                  | NA                        | WSA4                     | 26-E                                                     |

Notes: 30.0 through 225.0 kVA TP1 compliant

① Wall mounting brackets are available for these sizes, refer to page 165.