

111-04140

HellermannTyton



Article Number: 111-04140

Description: High Temp Cable Tie, 8.3" Long, 40lb Tensile Strength, PA66HS, Black, 1000/pkg

Base Data		
	Local Order Number	T40R0HSM4
	Type	T40R(U)
	Color	Black (BK)
	Features and Benefits	• Heat stabilized cable ties provide excellent resistance to high heat exposures. • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	High Temp Cable Tie, 8.3" Long, 40lb Tensile Strength, PA66HS, Black, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	40.0lbs
	Minimum Tensile Strength (Metric)	180.0N
	Length L (Imperial)	8.3"
	Length L (Metric)	212.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.16"
	Width W (Metric)	4.0mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm

111-04140

HellermannTyton

Product Dimensions	Bundle Diameter Max. (Imperial)	2.2"
	Bundle Diameter Max. (Metric)	55.0mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +257°F (-40°C to +125°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-ZODZ2.E64139
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987