


Capacitor, tantalum, 6.8 uF, 6032, +/-20% Tol, 16V@85C



Cutout at KEMET's option (either end); see note about P and R dimensions and cutout.

Dimensions (mm)

Specifications

ID.	D:	Talamanaa	Manager	KENAET
ID	Dimension	Tolerance	Manufacturer:	KEMET
L	6	+/-0.3	Capacitance:	6.8 uF
W	3.2	+/-0.3	Voltage DC @ 85C:	16V
Н	2.5	+/-0.3	Voltage DC @ 105C:	13V
K	1.4	+/-0.2	Voltage DC @ 125C:	10V
F	2.2	+/-0.1	Tolerance:	+/-20%
S	1.3	+/-0.3	Application:	General Purpose
В	0.5	+/-0.15	Body Type:	Molded Chip
X	0.1	ref	Temperature Range:	-55/+125C
Р	0.9	ref	Footprint:	6032
R	1	ref	Termination:	Tin
T	0.13	ref	Leakage Current:	1.1 uA
Α	2.5	ref	Dissipation Factor:	6%
G	2.8	ref	Impedance @ 100kHz:	2.4 Ohm
E	2.4	ref	Package Kind:	T&R
			Package Quantity:	750

Notes:

-C

