

117-05401

Article Number: 117-05401

Description: Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Black, 1000/pkg



Base Data	
Local Order Number	T50LDH0M4
Type	T50LDH
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• The tie contains a dual locking design to secure two bundles at once.</li> <li>• Head design can also provide spacing between parallel bundles.</li> <li>• Bent tail allows for quick insertion into head.</li> </ul>
Quantity Per	bag
Product Description	The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Black, 1000/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	15.6"
Length L (Metric)	395.0mm
Bundle Diameter 2nd Loop Max. (Imperial)	2.0"
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19"
Width W (Metric)	4.7mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.6mm

117-05401



Product Dimensions	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	50.0mm
	Bundle Diameter 1st Loop Max. (Imperial)	4.0"
	Bundle Diameter 1st Loop Max. (Metric)	101.6mm
	Bundle Diameter 2nd Loop Max. (Metric)	50.8mm
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987