

117-05461

Article Number: 117-05461

Description: Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg



| Base Data                                |   |
|--|---|
| Local Order Number                       | T50LDH9M4   |
| Type                                     | T50LDH  |
| Color                                    | Natural (NA)  |
| Features and Benefits                    | <ul style="list-style-type: none"> <li>• The tie contains a dual locking design to secure two bundles at once.</li> <li>• Head design can also provide spacing between parallel bundles.</li> <li>• Bent tail allows for quick insertion into head.</li> </ul>  |
| Quantity Per                             | bag   |
| Product Description                      | The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description                        | Double Head Tie, 15.6" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg   |
| Product Dimensions                       |   |
| Minimum Tensile Strength (Imperial)      | 50.0lbs   |
| Minimum Tensile Strength (Metric)        | 225.0N  |
| Length L (Imperial)                      | 15.6"   |
| Length L (Metric)                        | 395.0mm   |
| Bundle Diameter 2nd Loop Max. (Imperial) | 2.0"  |
| Fixation Method                          | None  |
| Identification Plate Position            | none  |
| Releasable Closure                       | No  |
| Tie Closure                              | plastic pawl  |
| Variant                                  | Inside Serrated   |
| Width W (Imperial)                       | 0.19"   |
| Width W (Metric)                         | 4.7mm   |
| Bundle Diameter Min. (Imperial)          | 0.06"   |
| Bundle Diameter Min. (Metric)            | 1.6mm   |

117-05461



|                               |  |                      |
|-------------------------------|--|----------------------|
| Product Dimensions            | Bundle Diameter Max. (Imperial)          | 2.0"                 |
|                               | Bundle Diameter Max. (Metric)            | 50.0mm               |
|                               | Bundle Diameter 1st Loop Max. (Imperial) | 4.0"                 |
|                               | Bundle Diameter 1st Loop Max. (Metric)   | 101.6mm              |
|                               | Bundle Diameter 2nd Loop Max. (Metric)   | 50.8mm               |
|                               | Thickness T (Metric)                     | 1.4mm                |
| Material and Specifications   |  |                      |
|                               | Material                                 | Polyamide 6.6 (PA66) |
|                               | Material Shortcut                        | PA66                 |
|                               | Flammability                             | UL94 V2              |
|                               | Halogenfree                              | Yes                  |
|                               | REACH Compliant (Article 33)             | Yes                  |
|                               | ROHS Compliant                           | Yes                  |
|                               | Certification/Specification              | UL   ANSI/UL 1565    |
| UL Recognized (US and Canada) | Yes                                      |                      |
| Logistic and Packaging        |  |                      |
|                               | Package Quantity (Metric)                | 1000Pieces           |
|                               | Customs Number(Schedule B)               | 3926909987           |