

805-0990
T50R0UVC2

Cable Tie, 50 lb. 7.9" Max. Bun. Dia. 1.97", PA66UV, Black, 100/pk

Article Number: 112-05060

Part Number: T50R0UVC2

Type: T50R



Base Data

Part No.	T50R0UVC2
Type	T50R
Color	Black
Features	HellermannTyton offers cable ties made of UV stabilized PA66 material. This provides additional protection against UV radiation for long term outdoor use and is available in various tensile strengths and bundle diameters.
Application	Used to bundle and secure wire and cable.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No

Tie Closure	plastic pawl
Variant	Inside Serrated

Product Dimensions

Min. Tensile Strength	50 lbs / 225 N
Length (L)	7.9 " / 200 mm
Width (W)	0.18 " / 4.6 mm
Min. Ø Bundle	0.06 " / 1.5 mm
Max. Ø Bundle	1.97 " / 50.0 mm
Thickness	1.2 mm

Material and Specifications

Material	Polyamide 6.6 UV-stabilized (PA66UV)
Certification	MIL 53421 / UL ZODZ2.E64139
CSA Certified	No
Flammability	UL94 V2
Material Specification	HF / RoHS
Operating Temperature	-40 °C to +85 °C, intermittent +105 °C (for 500 h)
ROHS Conformity	 RoHS