

111-85469

Article Number: 111-85469

Description: Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag



Base Data	Local Order Number	T50SL6.NN6P
	Type	T50SL6
	Color	Natural (NA)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Wing design helps stabilize the tie in high vibration applications</li> <li>• Includes a ladder type strap as opposed to a conventional serrated strap; providing the benefit of being extra flexible.</li> <li>• Design of tie provides low insertion and high extraction force.</li> </ul>
	Quantity Per	bag
	Product Description	Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.
	Short Description	Wing Push Mount Tie, 6.5" Long, 50lb Tensile, PA66, Natural, 500/bag
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225N
Length L (Imperial)		6.5"
Length L (Metric)		165mm
Fixation Method		Arrowhead
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.6mm
Width W2 (Imperial)		0.73"
Width W2 (Metric)		18.5mm
Bundle Diameter Min. (Imperial)		0.06"

111-85469



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	1.3"
	Bundle Diameter Max. (Metric)	34.0mm
	Disc Diameter (Imperial)	0.73"
	Disc Diameter (Metric)	18.5mm
	Panel Thickness Max. (Imperial)	0.1"
	Panel Thickness Max. (Metric)	2.5mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.5mm
	Mounting Hole Diameter D (Imperial)	0.25 - 0.3"
	Mounting Hole Diameter D (Metric)	6.3 - 7.5 mm
	Mounting Hole Diameter D Min. (Imperial)	0.25"
	Mounting Hole Diameter D Max. (Imperial)	0.3"
	Thickness T (Imperial)	0.05"
	Mounting Hole Diameter D Max. (Metric)	7.5mm
	Mounting Hole Diameter D Min. (Metric)	6.3mm
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987