

Thyristors

T70

Technical Data

Typical applications : D.C. Motor control, Controlled rectifiers, A.C. Controllers

Type No.	V_{RRM} (Volts)	V_{RSM} (Volts)
T70/04	400	500
T70/06	600	700
T70/08	800	900
T70/10	1000	1100
T70/12	1200	1300
T70/14	1400	1500
T70/16	1600	1700






Features





- Hermetic glass to metal seal
- Voltage grade upto 1600V
- Weight 80 gm (Approx)

Symbol	Conditions	Values
$I_{T(AV)}$	Sin 180 ; $T_{case} = 85^{\circ}C$	70 A
I_{TSM}	$T_{vj} = 25^{\circ}C$ $T_{vj} = 130^{\circ}C$	1300 A 1100 A
I^2t	$T_{vj} = 25^{\circ}C$ $T_{vj} = 130^{\circ}C$	8500 A ² s 6000 A ² s
I_{GT} V_{GT} dv/dt $[di/dt]_{CR}$	$T_{vj} = 25^{\circ}C$; $V_{DRM} = 5V$ $T_{vj} = 25^{\circ}C$; $V_{DRM} = 5V$ $T_{vj} = 125^{\circ}C$; Voltage = 67 % V_{DRM}	150 mA 3V *200 V/ μ s 50 A/ μ s
V_T V_0 R_0 I_{RRM}/I_{DRM}	$T_{vj} = 25^{\circ}C$; $I_T = 200A$ $T_{vj} = 130^{\circ}C$ $T_{vj} = 130^{\circ}C$ $T_{vj} = 130^{\circ}C$	1.80 V max 0.90 V 4 mW 25 mA
I_H I_L		Typ 150 mA; max. 250 mA Typ 300 mA; max. 600 mA
$R_{th(j-c)}$ $R_{th(c-h)}$ T_{vj} T_{stg}	Cont. Sin 180 / rec. 120	0.40 $^{\circ}C/W$ 0.47 / 0.53 $^{\circ}C/W$ 0.08 $^{\circ}C/W$ + 130 $^{\circ}C$ -40.....+ 150 $^{\circ}C$
Mounting torque		10 Nm
Case outline		Q

* Higher dv/dt selection available on request







PACAKAGE DEATILS

DO NOT SCALE

All Dimensions in mm

