


Pot Capacitors, Tag Mounting

TA 6 KV_p to 8 KV_p

TB 6 KV_p to 8 KV_p

TC 6 KV_p to 8 KV_p

TE 6 KV_p to 8 KV_p



• Dimensions in millimeters (inches)

MATERIAL:

Capacitor elements made from Class 1 ceramic dielectric with noble metal electrodes.

Connection Terminals: Copper/brass, silver plated.


FINISH:

Noble metal electrodes completely lacquered. Insulating rim glazed.

MARKING:

Type designator, Capacitance value and tolerance, Rated voltage (peak value), Production date code, Ceramic material code, DRALORIC Logo.

TD 6 KV_p to 8 KV_p



MODEL	T. 020030	T. 020050	T. 020080
Length L ₁	30 (1.181)	50 (1.969)	80 (3.1500)
Length L ₂	15 ± 1.5 (0.591 ± 0.059)	25 ± 2 (0.984 ± 0.079)	40 ± 2 (1.575 ± 0.079)
Length L ₃	20 ± 1.5 (0.787 ± 0.059)	25 ± 2 (0.984 ± 0.079)	40 ± 2 (1.575 ± 0.079)
Length L ₄	46 ± 2 (1.811 ± 0.079)	55 ± 2 (2.165 ± 0.079)	85 ± 2 (3.346 ± 0.079)
Length L ₅	31 ± 2 (1.220 ± 0.079)	51 ± 2 (2.008 ± 0.079)	81 ± 2 (3.189 ± 0.079)
Length L ₆	36 (1.417)	56 (2.205)	86 (3.386)

ORDERING INFORMATION

TA 020080	8 KV _p	100 pF	± 20 %	R 7
MODEL	RATED VOLTAGE	CAPACITANCE VALUE	TOLERANCE	CERAMIC



T. 020030				
CERAMIC	CAPACITANCE VALUE [pF]	RATED VOLTAGE [KV _P]	RATED POWER* [KVA _r]	RATED CURRENT [A _{RMS}]
R 7	10	3	3.5	6
	16			
	20			
R 16	25	8	4.2	6
	40			
R 42	50	8	4.2	6
	60			
	80			
	100			
R 85	120	8	4.2	6
	160			
	200			
	250	7		
	300			
	400			

T. 020050				
CERAMIC	CAPACITANCE VALUE [pF]	RATED VOLTAGE [KV _P]	RATED POWER* [KVA _r]	RATED CURRENT [A _{RMS}]
R 7	20	8	5.6	6
	25			
R 16	40			
	50			
	60			
	80			
R 42	100	8	7.0	6
	160			
	200			
R 85	250	8	7.0	6
	300			
	400			
	500			
	600			

T. 020080				
CERAMIC	CAPACITANCE VALUE [pF]	RATED VOLTAGE [KV _P]	RATED POWER* [KVA _r]	RATED CURRENT [A _{RMS}]
R 7	40	8	8.5	7
	60			
R 16	80			
	100			
	120			
	160			
R 42	200	8	10.5	7
	250			
	300			
R 85	400	8	10.5	7
	500			
	600			
	1000			
	1200	7		

CAPACITANCE TOLERANCES: ± 20 %, ± 10 %, ± 5 %

Other capacitance values and tolerances are available on request



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.