

595-24100



Article Number: 595-24100

Description: Dot Matrix, Self-Laminating Label, 2.0" X .50" X 1.437", 4 Across, White, 5000/pkg



Base Data		
	Local Order Number	TAG24-100
	Type	TAG24
	Color	White (WH)
	Features and Benefits	• Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
	Quantity Per	pack
	Product Description	Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.
	Short Description	Dot Matrix, Self-Laminating Label, 2.0" X .50" X 1.437", 4 Across, White, 5000/pkg
Product Dimensions		
	Length L (Imperial)	1.437"
	Length L (Metric)	36.5mm
	Self adhesive (Yes/No)	Yes
	Variant	Adhesive label
	Width W (Imperial)	2.0"
	Width W (Metric)	50.8mm
	Height H (Imperial)	0.5"
	Height H (Metric)	12.7mm
	Height H2 (Imperial)	1.437"
	Height H2 (Metric)	36.5mm
	Height of printable area (metric)	12.70mm
	Bundle Diameter Min. (Imperial)	0.14"
	Bundle Diameter Min. (Metric)	3.80mm

595-24100



Product Dimensions	Bundle Diameter Max. (Imperial)	0.29"
	Bundle Diameter Max. (Metric)	7.60mm
	Outside Diameter Min. (Imperial)	0.14"
	Outside Diameter Min. (Metric)	3.8mm
	Outside Diameter Max. (Imperial)	0.29"
	Outside Diameter Max. (Metric)	7.60mm
	Horizontal Repeat HR (metric)	50.80mm
	Horizontal Repeat HR (imperial)	2.000"
	Print Method	Dot-Matrix
	Thickness T (Metric)	75.0µm
	Vertical Repeat VR (metric)	38.10mm
	Vertical Repeat VR (imperial)	1.5"
	Width of Liner WL (imperial)	8.9"
	Width of Liner WL (metric)	228.60mm
Material and Specifications		
	Material	Type 100, Vinyl (PVC), white (WH), self laminating
	Material Shortcut	100
	Adhesive	Acrylic
	Adhesive Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
Logistic and Packaging		
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919905060
	Labels per Column	4
	Labels per Row	4
	Weight (Metric)	0.46kg