

595-26100



Article Number: 595-26100

Description: Dot Matrix, Self-Laminating Label, .50" X .375" X .75", 14 Across, White, 5000/pkg



Base Data		
	Local Order Number	TAG26-100
	Type	TAG26
	Color	White (WH)
	Features and Benefits	• Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
	Quantity Per	pack
	Product Description	Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.
	Short Description	Dot Matrix, Self-Laminating Label, .50" X .375" X .75", 14 Across, White, 5000/pkg
Product Dimensions		
	Length L (Imperial)	0.75"
	Length L (Metric)	19.05mm
	Self adhesive (Yes/No)	Yes
	Variant	Adhesive label
	Width W (Imperial)	0.5"
	Width W (Metric)	12.7mm
	Height H (Imperial)	0.375"
	Height H (Metric)	9.52mm
	Height H2 (Imperial)	0.75"
	Height H2 (Metric)	19.0mm
	Height of printable area (metric)	9.50mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.50mm

595-26100

HellermannTyton

Product Dimensions	Bundle Diameter Max. (Imperial)	0.118"
	Bundle Diameter Max. (Metric)	3.00mm
	Outside Diameter Min. (Imperial)	0.059"
	Outside Diameter Min. (Metric)	1.5mm
	Outside Diameter Max. (Imperial)	0.11"
	Outside Diameter Max. (Metric)	3.00mm
	Horizontal Repeat HR (metric)	15.24mm
	Horizontal Repeat HR (imperial)	.600"
	Print Method	Dot-Matrix
	Thickness T (Metric)	75.0µm
	Vertical Repeat VR (metric)	25.40mm
	Vertical Repeat VR (imperial)	1.0"
	Width of Liner WL (imperial)	9.3"
	Width of Liner WL (metric)	238.80mm
Material and Specifications		
	Material	Type 100, Vinyl (PVC), white (WH), self laminating
	Material Shortcut	100
	Adhesive	Acrylic
	Adhesive Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
Logistic and Packaging		
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919905060
	Labels per Column	14
	Labels per Row	14
	Weight (Metric)	0.28kg