

557-00042



Article Number: 557-00042

Description: Spirit Printer Label, .9" X .25", Polyester, White, 750/RL



Base Data		
	Local Order Number	TAGH16-336
	Type	TAGH16
	Color	White (WH)
	Features and Benefits	• Spirit portable printing system includes a white and metalized polyester film for surviving harsh environments. • Labels can withstand up to 300F continuous operating temperature for durable, extreme-environment use. • The printed labels are thicker making them perfect for marking almost any flat or slightly curved application. • Printed labels are UV stable which means that they can survive direct exposure to sunlight and the elements for up to 2 years. • Printing using the HHIGR will create a UL recognized mark for long term durability and chemical resistance.
	Quantity Per	reel
	Product Description	The HellermannTyton Spirit printing system is easy to use and features a "What You See Is What You Get" (WYSIWYG) user interface that shows the outline of the label on the LCD screen for quick and easy editing and printing. The Spirit 2100 provides a fast, high quality, thermal transfer printing of labels that are designed to survive industrial environments. A wide variety of label materials, sizes and types are available to fit most applications.
	Technical Description	Spirit Printer Label, .9" X .25", White
	Short Description	Spirit Printer Label, .9" X .25", Polyester, White, 750/RL
Product Dimensions		
	Length L (Imperial)	0.25"
	Length L (Metric)	6.35mm
	Variant	Roller form
	Width W (Imperial)	0.9"
	Width W (Metric)	22.86mm
	Height H (Imperial)	0.25"
	Height H (Metric)	6.35mm
	Height of printable area (metric)	6.35mm
	Print Method	Thermal Transfer

557-00042

HellermannTyton

Product Dimensions	Width of Liner WL (imperial)	1.125"
	Width of Liner WL (metric)	26.03mm
Material and Specifications		
	Material	Type 336, Polyester, white (WH)
	Material Shortcut	336
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
Logistic and Packaging		
	Package Quantity (Imperial)	750
	Package Quantity (Metric)	750
	Customs Number(Schedule B)	-
	Weight (Metric)	0.3kg