

TAT-125

**Adhesive-Lined,
Flexible,
Polyolefin Tubing**

Product Facts

- 2:1 shrink ratio
- Thin adhesive lining that bonds to outer tubing and surface below, forming a positive environmental seal
- Flexibility of both tubing and adhesive
- Moisture seal that is resistant to bending of the substrate
- Good mechanical strength and cut-through resistance
- Adhesive that bonds to a wide variety of plastics, rubbers, and metals, including polyethylene, neoprene, lead, and steel
- RoHS compliant



Heat-shrinkable Tubing

Applications

Seals and protects simple in-line splices, bimetallic joints, and components from fluids, moisture, and corrosion. Repairs damaged wire insulation, especially where flexibility is required. Provides one-step electrical insulation and moisture sealing.

Installation

Minimum shrink temperature: 95°C [203°F]
Minimum full recovery temperature: 121°C [250°F]

Operating Temperature Range

-55°C to 110°C
[-67°F to 230°F]

Specifications/Approvals

Series	UL* 	Military	Raychem
TAT-125 Type 1 (colors)	E85381 600 V, 125°C	AMS-DTL-23053/4*, Class 2	RW-3032
TAT-125 Type 2 (clear)	—	—	RW-3032

*Formerly MIL-I-23053/4 and MIL-DTL-23053/4. Sizes 1/4" through 1 1/2" only.

Available in:	Americas	Europe	Asia Pacific
	■		■

TAT-125 (Continued)

Product Dimensions

Size	Inside Diameter		Recovered Wall Thickness**	
	Minimum Expanded as Supplied	Maximum Recovered After Heating	Total Wall After Heating (Nominal)	Adhesive Wall After Heating (Nominal)
1/8	3.2 [0.125]	1.6 [0.062]	0.69 [0.027]	0.23 [0.009]
3/16	4.8 [0.187]	2.4 [0.093]	0.71 [0.028]	0.25 [0.010]
1/4	6.4 [0.250]	3.2 [0.125]	0.74 [0.029]	0.13 [0.005]
3/8	9.5 [0.375]	4.8 [0.187]	0.74 [0.029]	0.13 [0.005]
1/2	12.7 [0.500]	6.4 [0.250]	0.76 [0.030]	0.15 [0.006]
3/4	19.1 [0.750]	9.5 [0.375]	0.89 [0.035]	0.15 [0.006]
1	25.4 [1.000]	12.7 [0.500]	1.07 [0.042]	0.20 [0.008]
1 1/2	38.1 [1.500]	19.1 [0.750]	1.19 [0.047]	0.28 [0.011]

**Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard	Black (-0)
	Nonstandard	White (-9), red (-2), blue (-6), yellow (-4), green (-5), brown (-1), orange (-3), violet (-7), gray (-8), clear (-X, not flame-retardant)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.	
Standard packaging	In 1.2-meter [4-foot] lengths.	
Ordering description	Specify product name, size and color (for example, TAT-125 1/4-0).	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

[TAT-125-1/4-0-STK](#) [TAT-125-1/8-0-STK](#) [TAT-125-1/2-0-STK](#) [TAT-125-3/4-0-STK](#) [TAT-125-3/8-0-STK](#) [TAT-125-3/16-0-STK](#) [TAT-125-3-0-STK](#) [TAT-125-1/4-0-SP](#) [TAT-125-1/2-2-STK](#) [TAT-125-1/8-0-SP](#) [TAT-125-1-0-STKCS5451](#) [TAT-125-2-0-STK](#) [TAT-125-3/16-0-SP](#) [TAT-125-3/8-0-1IN](#) [TAT-125-1-0-STK](#) [TAT-125-1-1/2-0-STK](#) [TAT-125-1-1/2-2-STK](#) [TAT-125-3/4-0-2.5IN](#) [TAT-125-3/16-0-1.5IN](#) [TAT-125-3/4-2-STK](#) [TAT-125-3/8-0-2IN](#) [TAT-125-3/16-6-STK](#) [TAT-125-1/4-0-STK-CS6171](#) [TAT-125-1/2-0-STK-CS7373](#) [TAT-125-3/8-0-STK-CS6171](#) [TAT-125-3/8-0-STKCS5451](#) [TAT-125-3/8-X-STK](#) [TAT-125-1/4-0-STK-CS7350](#) [TAT-125-3-0-STK-CS7350](#) [TAT-125-1/8-0-STK-CS7350](#) [TAT-125-3-5-STK](#) [TAT-125-3/4-X-STK](#) [TAT-125-1/2-0-STK-CS7796](#) [TAT-125-1-0-STK-CS7350](#) [TAT-125-3/16-9-SP](#) [TAT-125-1-1/2-0-STKCS5451](#) [TAT-125-2-0-STK-CS5577](#) [TAT-125-1/4-X-STK-CS7450](#) [TAT-125-3/4-0-STK-CS7796](#) [TAT-125-1/2-0-STK-CS6171](#) [TAT-125-1/8-9-SP](#) [TAT-125-1/8-X-STK](#) [TAT-125-1/4-0-STK-CS7373](#) [TAT-125-1/2-0-STK-CS7350](#) [TAT-125-2-0-STK-CS7373](#) [TAT-125-1-1/2-0-STKCS6931](#) [TAT-125-1/8-0-STK-CS7425](#) [TAT-125-3/8-X-STK-CS7450](#) [TAT-125-3/16-X-STK](#) [TAT-125-3/16-0-STK-CS6171](#) [TAT-125-3/4-0-STK-CS7373](#) [TAT-125-3/4-9-STK](#) [TAT-125-1/4-2-STK](#) [TAT-125-1/4-9-STK](#) [TAT-125-3/16-X-SP](#) [TAT-125-3/16-9-STK](#) [TAT-125-1-1/2-9-STK](#) [TAT-125-3/8-0-1.5IN](#) [TAT-125-3/8-2-STK](#) [TAT-125-3/4A-0-ASP](#) [TAT-125-3/4-0-STK-CS7350](#) [TAT-125-2-0-STK-CS5451](#) [TAT-125-1/2-X-STK](#) [TAT-125-3-5-STK-CS9250](#) [TAT-125-3/8-0-STK-CS7335](#) [TAT-125-1-6-STK](#) [TAT-125-1-9-STK](#) [TAT-125-3/4-6-STK](#) [TAT-125-3/8-0-SP](#)