



- NOTES:
- ENCLOSURE MATERIAL: CLEAR UV RESISTANT POLYCARBONATE.
 - MOUNTING CLIP INCLUDED : 2 PER FOOT.
 - MOUNTING SCREWS NOT INCLUDED : #10 SELF TAPPING WOOD SCREW RECOMMENDED.
 - ENCLOSURE IS SEALED AND WATER RESISTANT.
 - FOR CONNECTING WIRES ON BOTH ENDS THE SAMPLE PART# IS TBL312FC-XXX-012V (FROSTED)

TBL312F-XPW-012V	WHITE	8000K	12.6" [320.04mm]	12VDC	0.16 A	1.92 W	85/90°		
TBL312F-2IW-012V	WARM WHITE	3000K	12.6" [320.04mm]	12VDC	0.16 A	1.92 W	85/90°		
LEDTRONICS PART NO.	COLOR	TEMP.	"L" INCH & [mm]	VOLTAGE	Amps.	WATTS	VIEW ANGLE TYP.	LUMINOUS TOTAL	cd TOTAL



LEDTRONICS, INC.
23108 KASHIMURA COURT
TORRANCE, CA 90505

PROPRIETARY:
This document contains proprietary information of LEDTRONICS, INC. and is disclosed for your information only. It is not to be reproduced or used in any manner without the prior express written consent of LEDTRONICS, INC.

XXX ± .010 TOLERANCE PER ANSI-Y14.5
XX ± .025 (UNLESS OTHERWISE STATED)
FRACT. ± 1/32

TITLE			
TBL312F-XXX-012V (FROSTED)			
DWG NO	SCALE	SHEET	DATE
TBL312002-CUST	1:2	1 OF 1	01-27-06
CODE	DWG BY	CHK BY	CUSTOMER
82410	AM/RM	03-13-06	

REVISION NOTIFICATION	
☐ PMA	
☐ UL	
☐ CUSTOMER	
☐ OTHER	