

T&B° Fittings

T&B Catalog Number: TCF100-88AL 78621087950 Description: 1" Aluminum Tra

1" Aluminum Tray/Cord Fitting. Cable diameter (minimum)-.770; (maximum)-.880.

, , , ,

Status: Active

Features	
i catalos	Hand-tightens-no tools required
	Tapered neoprene bushing and O-ring seal out
	moisture and dirt ingress.
	Corrosion-resistant, non-magnetic aluminum con-
	struction
	Chuck grip provides high mechanical pull-out per- formance which exceeds applicable requirements.
Application	
	Silver Grip® Tray/Cord fitting is the safe and cost effective choice for increased safety when terminating portable cord and try cable in hazardous locations. Designed for use in Class I, Gas and Vapor environments, the Silver Grip® Tray/Cord fitting provides efficent strain relief for cables entering enclosure and raceways, and for cords used on portable equipment.
General	
Material	Aluminum
Dimension Information	
Hub Size (inches)	1
Cable Opening-Minimum (inches)	0.770
Cable Opening-Maximum (inches)	0.880
Throat Diameter (inches)	0.980
Packaging	
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	36.38 lbs. per 100
Application Support	
Product Overview	Available on Website
Notes	
*Note	Tray cable is not suitable for use in Zone 1 locations. Portable cord can be used in Zone 1 applications only when installed on portable equipment.
Certifications	
RoHS Compliance	No

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com