Type TCG Axial Leaded Aluminum Electrolytic Capacitors

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any quarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly sclaims any guarantee, warranty or representation concerning the suitability for a specific customer as lication, use, storage, transportation, or operating environment. The Information is intended for se only customers who have the requisite experience and capability to determine the correct page 1 ucts for the technical advice inferred from this Information or otherwise provide by Co ell Dubilie, with reference to the use of any Cornell Dubilier products is given gratis (unless herwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the antice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design. and manufacturing of its products, in light of the current state art, is ated component failures may still occur. Accordingly, customer applications which require a high slegrez of reliability or safety should employ suitable designs or other safeguards (such a stallation of stective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component chough all product-related warnings, does not result in a risk of personal injury or ald not assume that all safety measures are indicautions and notes must be observed, the astomer sh cated in such warnings, cautions and notes or that other safety measures may not be required.