Home > Products > Relays > Product Feature Selector > Product Details

TD229-6002P Product Details

Share   Print   Email

✔ **Active**

📄 **View 3D PDF**

Time Delay Relays

TD229-6002P=TDFR 60 SEC

TD229-6002P
TE Internal Number: 1-1617806-5

Product Highlights View All

- TD2 Series Time Delay Series
- Input Voltage = 20 - 30 VDC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 28 VDC or 115VAC
- Mounting Options = Raised Vertical Flange Mount

Pricing & Availability ▶

Request Sample ▶

Add to My Part List +

Buy Product through Distributor ▶

Feedback

Related Products

Not quite the product you're looking for?

Find Similar Products

View Part in Product Feature Selector

Check for Tooling

| Documents | **Features** | Compliance |

Please Note:
Use the Product Drawing for all design activity

Mechanical Attachment

Mounting Options	Raised Vertical Flange Mount

Electrical Characteristics

Input Voltage (VDC)	20 – 30
Contact Rating	10A @ 28 VDC or 115VAC

Termination Features

Termination Type	Socket Pin Terminal

Dimensions ◢

Approx. Dimensions (L x W x H) (mm [in])	25.79 x 25.79 x 25.4 [1.015 x 1.015 x1.00]

Contact Features

Delay Time	60 seconds
Type of Control	Fixed
Repeatability, Max.	± 10%

Configuration Features

Contact - Arrangement ?	2 Form C, DPDT, 2 C/O
Multiple Timing Ranges	Without

Industry Standards

Approved Standards	MIL-PRF-8372/29, MIL-STD-1686 Class Non Sensitive
RoHS/ELV Compliance ?	Not reviewed for ELV/RoHS compliance
Lead Free Solder Processes ?	Not reviewed for lead free solder process

Conditions for Usage

Temperature Range (°C)	-55 – +125

Operation/Application

Mode of Operation	Delay on Release

Other

Series	TD2 Series Time Delay
Brand	CII