




TEMPERATURE	RESISTANCE (OHMS)
-30°C (-22°F)	1649±11 (1.7°C)
-20°C (-4°F)	1715±10 (1.5°C)
-10°C (14°F)	1784±9 (1.3°C)
0°C (32°F)	1854±8 (1.1°C)
+10°C (50°F)	1926±6 (0.8°C)
+20°C (68°F)	2000±5 (0.7°C)
+30°C (86°F)	2076±5 (0.7°C)
+40°C (104°F)	2153±6 (0.8°C)
+50°C (122°F)	2233±7 (0.9°C)
+60°C (140°F)	2314±9 (1.1°C)
+70°C (158°F)	2397±10 (1.2°C)
+80°C (176°F)	2482±12 (1.4°C)
+90°C (194°F)	2569±14 (1.6°C)
+100°C (212°F)	2658±16 (1.8°C)

T = TEMPERATURE IN °C

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH		THIRD ANGLE PROJECTION 	
CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	
OPERATING FORCE DIFFERENTIAL FORCE RELEASE FORCE PRETRAVEL DIFFERENTIAL TRAVEL OVERTRAVEL FREE POSITION	CONTACT ARRANGEMENT	DO NOT SCALE PRINT	
		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
		ONE PLACE (.0) ±.030	
		TWO PLACE (.00) ±.015	
		THREE PLACE (.000) ±.005	
		ANGLES ±	
		WEIGHT	

ANSI Y14.5M-1982 APPLIES

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[TD4S-L](#)